

**CLI C 2-4 GE/SW X CD****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

Similar to illustration

CLI C conductor markers are mounted on unconnected conductors. Four different sizes are available for labelling conductor cross-sections from 0.5 mm<sup>2</sup> to max. 70 mm<sup>2</sup>. The markers are already printed and ready for use. Individual labelling is possible by combining the individual markers.

- Closed markers, reliable and for mounting on unconnected cables
- A special flexible bellows profile ensures a wide application range
- Fast and easy to fit – with minimal effort
- Corresponding accessories make labelling easy
- Permanent, high-quality labelling
- High contrast for optimum legibility

**General ordering data**

|            |                                                                                                                             |
|------------|-----------------------------------------------------------------------------------------------------------------------------|
| Version    | CableLine, Conductor and cable markers, 4 - 10 mm, {Reference (AttributeDefinition) not found: pAttr74196859207437}, yellow |
| Order No.  | <a href="#">1568261687</a>                                                                                                  |
| Type       | CLI C 2-4 GE/SW X CD                                                                                                        |
| GTIN (EAN) | 4008190143756                                                                                                               |
| Qty.       | 250 pc(s).                                                                                                                  |

Creation date March 24, 2021 6:29:08 AM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

## CLI C 2-4 GE/SW X CD

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|                |            |                 |            |
|----------------|------------|-----------------|------------|
| Depth          | 8 mm       | Depth (inches)  | 0.315 inch |
| Height         | 4 mm       | Height (inches) | 0.157 inch |
| Net weight     | 0.214 g    | Width           | 7 mm       |
| Width (inches) | 0.276 inch |                 |            |

## Temperatures

|                             |             |
|-----------------------------|-------------|
| Operating temperature range | -30...80 °C |
|-----------------------------|-------------|

## General data

|                                   |                                      |                                              |                    |
|-----------------------------------|--------------------------------------|----------------------------------------------|--------------------|
| Colour                            | yellow                               | Colour of printing                           | black              |
| Halogen                           | Yes                                  | Insulation cross-section, max.               | 10 mm              |
| Material                          | PVC, soft, without Cadmium           | Material colour according to resistance code | 4                  |
| Number of markers per combination | 1 Reel = Conductor and cable markers | Operating temperature range                  | -30...80 °C        |
| Operating temperature range, max. | 80 °C                                | Operating temperature range, min.            | -30 °C             |
| Orientation of print              | horizontal                           | Printed characters                           | Upper-case letters |
| Printing                          | X                                    | Printing method                              | hot-embossing      |
| Recommended industries            | Process, Machinery                   | Type of printing                             | Standard           |
| UL 94 flammability rating         | V-0                                  | Version                                      | CD                 |
| Width                             | 7 mm                                 |                                              |                    |

## Conductor and cable markers

|                               |                     |                                  |                          |
|-------------------------------|---------------------|----------------------------------|--------------------------|
| Conductor O.D.                | 4 - 10 mm           | Conductor O.D., max.             | 10 mm                    |
| Conductor O.D., min.          | 4 mm                | Conductor cross-section, max.    | 16 mm <sup>2</sup>       |
| Conductor cross-section, min. | 2.5 mm <sup>2</sup> | Cross-section for connected wire | 2.5 - 16 mm <sup>2</sup> |
| Halogen                       | Yes                 |                                  |                          |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001530    | ETIM 7.0    | EC001530    |
| ECLASS 9.0  | 27-40-04-01 | ECLASS 9.1  | 27-40-04-01 |
| ECLASS 10.0 | 27-40-04-01 | ECLASS 11.0 | 27-28-11-02 |

## Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## Downloads

|                             |                                                                      |
|-----------------------------|----------------------------------------------------------------------|
| Engineering Data            | <a href="#">EPLAN, WSCAD</a>                                         |
| Product Change Notification | <a href="#">PCN CableLine_DE</a><br><a href="#">PCN CableLine_EN</a> |

### CLI C 2-4 GE/SW X CD

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings



Similar to illustration