

**WAP WDU1.5/BLZ/ZA****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Product image****Spring connection with PUSH IN Technology**

The innovative PUSH IN technology reduces the amount of time you spend on wiring to a minimum. Direct insertion guarantees high conductor pull-out forces and simple handling for all conductor types.

**General ordering data**

|            |                            |
|------------|----------------------------|
| Version    | W-Series, End plate        |
| Order No.  | <a href="#">1577320000</a> |
| Type       | WAP WDU1.5/BLZ/ZA          |
| GTIN (EAN) | 4008190073770              |
| Qty.       | 50 pc(s).                  |

## WAP WDU1.5/BLZ/ZA

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|                |            |                 |            |
|----------------|------------|-----------------|------------|
| Depth          | 37 mm      | Depth (inches)  | 1.457 inch |
| Height         | 45.4 mm    | Height (inches) | 1.787 inch |
| Net weight     | 1.821 g    | Width           | 2.5 mm     |
| Width (inches) | 0.098 inch |                 |            |

## Temperatures

|                                  |                |                                  |        |
|----------------------------------|----------------|----------------------------------|--------|
| Storage temperature              | -25 °C...55 °C | Continuous operating temp., min. | -50 °C |
| Continuous operating temp., max. | 120 °C         |                                  |        |

## Material data

|                           |       |        |            |
|---------------------------|-------|--------|------------|
| Material                  | Wemid | Colour | dark beige |
| UL 94 flammability rating | V-0   |        |            |

## System specifications

|         |           |
|---------|-----------|
| Version | End plate |
|---------|-----------|

## Additional technical data

|                     |                                            |         |    |
|---------------------|--------------------------------------------|---------|----|
| Installation advice | Feed-through (bushing),<br>Direct mounting | Snap-on | No |
|---------------------|--------------------------------------------|---------|----|

## General

|                     |                                            |
|---------------------|--------------------------------------------|
| Installation advice | Feed-through (bushing),<br>Direct mounting |
|---------------------|--------------------------------------------|

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000886    | ETIM 7.0    | EC000886    |
| ECLASS 9.1  | 27-14-11-33 | ECLASS 10.0 | 27-14-11-33 |
| ECLASS 11.0 | 27-14-11-33 |             |             |

## Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## Downloads

|                    |                                                                         |
|--------------------|-------------------------------------------------------------------------|
| Engineering Data   | <a href="#">18503_WAP_WDU1.5-BLZ-ZA_DXF.dxf</a><br><a href="#">STEP</a> |
| Engineering Data   | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>                                |
| User Documentation | <a href="#">StorageConditionsTerminalBlocks</a>                         |