


# Flat cylinder DZH-20- -PPV-A-S20

Part number: 158380

FESTO



General operating condition

## Data sheet

Overall data sheet – Individual values depend upon your configuration.

| Feature                                      | Value                                                              |
|----------------------------------------------|--------------------------------------------------------------------|
| Stroke                                       | 1 mm ... 320 mm                                                    |
| Piston diameter                              | 20 mm<br>Equivalent diameter                                       |
| Piston rod thread                            | M8                                                                 |
| Max. angle of rotation of the piston rod +/- | 2.6 deg                                                            |
| Cushioning                                   | Pneumatic cushioning, adjustable at both ends                      |
| Mounting position                            | Any                                                                |
| Mode of operation                            | Double-acting                                                      |
| Structural design                            | Piston<br>Piston rod<br>Profile barrel                             |
| Position sensing                             | For proximity sensor                                               |
| Symbol                                       | 00991236                                                           |
| Variants                                     | Through, hollow piston rod                                         |
| Protection against torsion/guide             | Oval piston                                                        |
| Operating pressure                           | 0.1 MPa ... 1 MPa                                                  |
| Operating pressure                           | 1 bar ... 10 bar                                                   |
| Operating medium                             | Compressed air as per ISO 8573-1:2010 [7:4:4]                      |
| Information on operating and pilot media     | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC)             | 2 - Moderate corrosion stress                                      |
| LABS (PWIS) conformity                       | VDMA24364-B2-L                                                     |
| Ambient temperature                          | -20 °C ... 80 °C                                                   |
| Cushioning length                            | 17 mm                                                              |
| Max. torque for protection against rotation  | 0.6 Nm                                                             |
| Theoretical force at 6 bar, retracting       | 158 N                                                              |
| Theoretical force at 6 bar, advancing        | 158 N                                                              |
| Moving mass at 0 mm stroke                   | 76 g                                                               |
| Additional moving mass per 10 mm stroke      | 6.8 g                                                              |
| Additional weight per 10 mm stroke           | 18.7 g                                                             |
| Basic weight with 0 mm stroke                | 251 g                                                              |
| Type of mounting                             | With internal thread<br>With accessories                           |
| Pneumatic connection                         | G1/8                                                               |
| Note on materials                            | RoHS-compliant                                                     |
| Cover material                               | Aluminum                                                           |
| Seals material                               | TPE-U(PU)                                                          |

| Feature              | Value            |
|----------------------|------------------|
| Housing material     | Aluminum         |
| Piston seal material | TPE-U(PU)        |
| Piston rod material  | High-alloy steel |