

WKB 1/2**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Product image****WKB 1/2 160428****Current and voltage transformer wiring**

Our test disconnect terminal blocks featuring spring and screw connection technology allow you to create all the important converter circuits for measuring current, voltage and power in a safe and sophisticated way.

General ordering data

Version	Accessories, Cross-connection slider, Cross-connector accessories, Number of poles: 2
Order No.	1604280000
Type	WKB 1/2
GTIN (EAN)	4008190165338
Qty.	50 pc(s).

WKB 1/2

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	6.1 mm	Depth (inches)	0.24 inch
Height	9.3 mm	Height (inches)	0.366 inch
Net weight	1.4 g	Width	14.1 mm
Width (inches)	0.555 inch		

Temperatures

Continuous operating temp., min.	-50 °C	Continuous operating temp., max.	100 °C
----------------------------------	--------	----------------------------------	--------

Material data

Material	Polyamide 66	Colour	orange
UL 94 flammability rating	V-2		

System specifications

Version	Cross-connector accessories
---------	-----------------------------

Additional technical data

Explosion-tested version	No	Installation advice	Direct mounting
Type of fixing	Plugged	Type of mounting	Clamped

Dimensions

Pitch in mm (P)	8 mm	TS 35 offset	47 mm
-----------------	------	--------------	-------

General

Installation advice	Direct mounting	Number of poles	2
Operating temperature range, max.	100 °C		

Classifications

ETIM 6.0	EC000489	ETIM 7.0	EC000489
ECLASS 9.0	27-14-11-40	ECLASS 9.1	27-14-11-40
ECLASS 10.0	27-14-11-40	ECLASS 11.0	27-14-11-40

Approvals

Approvals



ROHS Conform

Downloads

Approval/Certificate/Document of Conformity	EAC certificate
Engineering Data	STEP
Engineering Data	EPLAN, WSCAD, Zuken E3.S
User Documentation	StorageConditionsTerminalBlocks

Creation date March 24, 2021 9:39:10 AM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.