


Linear actuator DGPL-18- -PPV-A-KF-B

Part number: 161977

FESTO



 [General operating condition](#)

Data sheet

Overall data sheet – Individual values depend upon your configuration.

Feature	Value
Stroke	10 mm ... 1800 mm
Piston diameter	18 mm
Cushioning	Pneumatic cushioning, adjustable at both ends Pneumatic shock absorber, hard characteristic curve
Mounting position	Any
Guide	Recirculating ball bearing guide
Driver principle	Positive locking (slot)
Position sensing	For proximity sensor
Symbol	00991254
Operating pressure	0.2 MPa ... 0.8 MPa
Operating pressure	2 bar ... 8 bar
Mode of operation	Double-acting
Operating medium	Compressed air as per ISO 8573-1:2010 [7:-:-]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	0 - No corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Ambient temperature	-10 °C ... 60 °C
Cushioning length	16 mm
Theoretical force at 6 bar, retracting	153 N
Theoretical force at 6 bar, advancing	153 N
Moving mass	360 g
Moving mass at 0 mm stroke	360 g
Additional moving mass per 10 mm stroke	36 g
Basic weight with 0 mm stroke	830 g
Alternative connections	See product drawing
Pneumatic connection	M5
Cover material	Cast aluminum Coated
Seals material	NBR TPE-U(PU)
Housing material	Anodized