


# Twin cylinder DPZ-16-10-P-A-KF-S2

Part number: 162033

FESTO



 General operating condition

## Data sheet

| Feature                                  | Value                                                              |
|------------------------------------------|--------------------------------------------------------------------|
| Stroke                                   | 10 mm                                                              |
| Adjustable end position range/length     | 10 mm                                                              |
| Piston diameter                          | 16 mm                                                              |
| Drive unit operating mode                | Yoke                                                               |
| Cushioning                               | Elastic cushioning rings/pads at both ends                         |
| Mounting position                        | Any                                                                |
| Guide                                    | Recirculating ball bearing guide                                   |
| Structural design                        | Guide                                                              |
| Position sensing                         | For proximity sensor                                               |
| Symbol                                   | 00991915                                                           |
| Variants                                 | Through piston rod                                                 |
| Operating pressure                       | 0.1 MPa ... 1 MPa                                                  |
| Operating pressure                       | 1 bar ... 10 bar                                                   |
| Mode of operation                        | Double-acting                                                      |
| Operating medium                         | Compressed air as per ISO 8573-1:2010 [7:4:4]                      |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC)         | 0 - No corrosion stress                                            |
| LABS (PWIS) conformity                   | VDMA24364-B1/B2-L                                                  |
| Ambient temperature                      | -20 °C ... 80 °C                                                   |
| Impact energy in the end positions       | 0.15 J                                                             |
| Theoretical force at 6 bar, retracting   | 180 N                                                              |
| Theoretical force at 6 bar, advancing    | 180 N                                                              |
| Alternative connections                  | See product drawing                                                |
| Pneumatic connection                     | M5                                                                 |
| Cover material                           | Wrought aluminum alloy                                             |
| Seals material                           | NBR                                                                |
| Housing material                         | Wrought aluminum alloy                                             |
| Piston rod material                      | Case-hardened steel                                                |