

Flat cylinder DZF-11/16"- -A-P-A

Part number: 162973

FESTO



 General operating condition

Data sheet

Overall data sheet – Individual values depend upon your configuration.

Feature	Value
Stroke	1.016 mm ... 203.2 mm
Piston diameter	11/16" Equivalent diameter
Piston rod thread	5/16-24 UNF-2A
Max. angle of rotation of the piston rod +/-	1.2 deg
Cushioning	Elastic cushioning rings/pads at both ends
Mounting position	Any
Mode of operation	Double-acting
Structural design	Piston Piston rod
Position sensing	For proximity sensor
Symbol	00991217
Variants	Piston rod at one end
Protection against torsion/guide	Oval piston
Operating pressure	0.1 MPa ... 1 MPa
Operating pressure	1 bar ... 10 bar
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	2 - Moderate corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Ambient temperature	-20 °C ... 80 °C
Impact energy in the end positions	0.10033 J
Max. torque for protection against rotation	0.2 Nm
Theoretical force at 6 bar, retracting	123.216 N
Theoretical force at 6 bar, advancing	153.019 N
Moving mass at 0 mm stroke	24 g
Moving mass with 0 inch stroke	0.85 oz
Additional moving mass per 10 mm stroke	4 g
Additional moving mass per 1 inch stroke	0.36 oz
Additional weight per 10 mm stroke	13 g
Additional weight per 1 inch stroke	1.16 oz
Basic weight with 0 mm stroke	107 g
Basic weight with 0 inch stroke	3.77 oz
Type of mounting	With internal thread With accessories

Feature	Value
Pneumatic connection	10-32 UNF-2B
Cover material	Wrought aluminum alloy
Seals material	NBR TPE-U(PU)
Housing material	Wrought aluminum alloy, anodized
Piston seal material	NBR
Piston rod material	High-alloy stainless steel