

Flat cylinder DZF-1 1 1/4"- -A-P-A

Part number: 162975

FESTO



 General operating condition

Data sheet

Overall data sheet – Individual values depend upon your configuration.

Feature	Value
Stroke	1.016 mm ... 330.2 mm
Piston diameter	1 1/4" Equivalent diameter
Piston rod thread	3/8-24 UNF-2A
Max. angle of rotation of the piston rod +/-	0.8 deg
Cushioning	Elastic cushioning rings/pads at both ends
Mounting position	Any
Mode of operation	Double-acting
Structural design	Piston Piston rod
Position sensing	For proximity sensor
Symbol	00991217
Variants	Piston rod at one end
Protection against torsion/guide	Oval piston
Operating pressure	0.1 MPa ... 1 MPa
Operating pressure	1 bar ... 10 bar
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	2 - Moderate corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Ambient temperature	-20 °C ... 80 °C
Impact energy in the end positions	0.39997 J
Max. torque for protection against rotation	0.8 Nm
Theoretical force at 6 bar, retracting	415.019 N
Theoretical force at 6 bar, advancing	483.077 N
Moving mass at 0 mm stroke	65 g
Moving mass with 0 inch stroke	2.29 oz
Additional moving mass per 10 mm stroke	9 g
Additional moving mass per 1 inch stroke	0.81 oz
Additional weight per 10 mm stroke	24 g
Additional weight per 1 inch stroke	2.15 oz
Basic weight with 0 mm stroke	272 g
Basic weight with 0 inch stroke	9.59 oz
Type of mounting	With internal thread With accessories

Feature	Value
Pneumatic connection	1/8 NPT
Cover material	Die-cast aluminum
Seals material	HNBR TPE-U(PU)
Housing material	Wrought aluminum alloy, anodized
Piston seal material	NBR
Piston rod material	High-alloy steel