


# Flat cylinder DZF-2"- -A-P-A

Part number: 162977

FESTO

Exemplary representation



General operating condition

## Data sheet

Overall data sheet – Individual values depend upon your configuration.

Feature	Value
Stroke	1.016 mm ... 330.2 mm
Piston diameter	2" Equivalent diameter
Piston rod thread	5/8-18 UNF-2A
Max. angle of rotation of the piston rod +/-	0.5 deg
Cushioning	Elastic cushioning rings/pads at both ends
Mounting position	Any
Mode of operation	Double-acting
Structural design	Piston Piston rod
Position sensing	For proximity sensor
Symbol	00991217
Variants	Piston rod at one end
Protection against torsion/guide	Oval piston
Operating pressure	0.1 MPa ... 1 MPa
Operating pressure	1 bar ... 10 bar
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	2 - Moderate corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Ambient temperature	-20 °C ... 80 °C
Impact energy in the end positions	0.63723 J
Max. torque for protection against rotation	1.2 Nm
Theoretical force at 6 bar, retracting	990.174 N
Theoretical force at 6 bar, advancing	1177.889 N
Moving mass at 0 mm stroke	219 g
Moving mass with 0 inch stroke	7.72 oz
Additional moving mass per 10 mm stroke	25 g
Additional moving mass per 1 inch stroke	2.24 oz
Additional weight per 10 mm stroke	64 g
Additional weight per 1 inch stroke	5.73 oz
Basic weight with 0 mm stroke	854 g
Basic weight with 0 inch stroke	30.12 oz
Type of mounting	With internal thread With accessories

<b>Feature</b>	<b>Value</b>
Pneumatic connection	1/4 NPT
Cover material	Die-cast aluminum
Seals material	NBR TPE-U(PU)
Housing material	Wrought aluminum alloy, anodized
Piston seal material	NBR
Piston rod material	High-alloy steel