

**STA 1/ZA SAK4-10****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Product image**

Similar to illustration

**Building installation wiring**

For building installations, we offer a complete system that revolves around the 10×3 copper rail and comprises perfectly coordinated components: from installation terminal blocks, neutral conductor terminal blocks and distribution terminal blocks to comprehensive accessories such as busbars and busbar holders.

**General ordering data**

|            |                            |
|------------|----------------------------|
| Version    | SAK Series, Test adapter   |
| Order No.  | <a href="#">1632450000</a> |
| Type       | STA 1/ZA SAK4-10           |
| GTIN (EAN) | 4008190209636              |
| Qty.       | 25 pc(s).                  |

## STA 1/ZA SAK4-10

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|                |            |                 |            |
|----------------|------------|-----------------|------------|
| Depth          | 79.5 mm    | Depth (inches)  | 3.13 inch  |
| Height         | 66.11 mm   | Height (inches) | 2.603 inch |
| Net weight     | 12.8 g     | Width           | 6.4 mm     |
| Width (inches) | 0.252 inch |                 |            |

## Temperatures

|                                  |                |                                  |        |
|----------------------------------|----------------|----------------------------------|--------|
| Storage temperature              | -25 °C...55 °C | Continuous operating temp., min. | -50 °C |
| Continuous operating temp., max. | 100 °C         |                                  |        |

## Environmental Product Compliance

|            |                |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

## Material data

|                           |       |        |       |
|---------------------------|-------|--------|-------|
| Material                  | PA 66 | Colour | beige |
| UL 94 flammability rating | V-2   |        |       |

## System specifications

|         |                   |
|---------|-------------------|
| Version | For the terminals |
|---------|-------------------|

## Additional technical data

|                     |                 |
|---------------------|-----------------|
| Installation advice | Direct mounting |
|---------------------|-----------------|

## Conductors for clamping (rated connection)

|                  |       |                       |                  |
|------------------|-------|-----------------------|------------------|
| Clamping screw   | M 2.5 | Number of connections | 1                |
| Stripping length | 6 mm  | Type of connection    | Screw connection |

## General

|                     |                 |                 |   |
|---------------------|-----------------|-----------------|---|
| Installation advice | Direct mounting | Number of poles | 1 |
|---------------------|-----------------|-----------------|---|

## Rating data

|               |       |
|---------------|-------|
| Rated voltage | 250 V |
|---------------|-------|

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC002555    | ETIM 7.0    | EC002555    |
| ECLASS 9.0  | 27-14-11-48 | ECLASS 9.1  | 27-14-11-48 |
| ECLASS 10.0 | 27-14-11-48 | ECLASS 11.0 | 27-14-11-48 |

## Approvals

Approvals



|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

### STA 1/ZA SAK4-10

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Downloads

Approval/Certificate/Document of  
Conformity

[EAC certificate](#)

[EAC certificate](#)

User Documentation

[StorageConditionsTerminalBlocks](#)