

**ZQS 2.5/4****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Product image****Klippon® Connect with clamping yoke Technology**

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

**General ordering data**

|            |                                    |
|------------|------------------------------------|
| Version    | Accessories, Cross-connector, 24 A |
| Order No.  | <a href="#">1633220000</a>         |
| Type       | ZQS 2.5/4                          |
| GTIN (EAN) | 4008190263409                      |
| Qty.       | 20 pc(s).                          |

## ZQS 2.5/4

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|                |           |                 |            |
|----------------|-----------|-----------------|------------|
| Depth          | 31.6 mm   | Depth (inches)  | 1.244 inch |
| Height         | 41 mm     | Height (inches) | 1.614 inch |
| Net weight     | 5.55 g    | Width           | 2.8 mm     |
| Width (inches) | 0.11 inch |                 |            |

## Temperatures

|                                  |                |                                  |     |
|----------------------------------|----------------|----------------------------------|-----|
| Storage temperature              | -25 °C...55 °C | Continuous operating temp., min. | -50 |
| Continuous operating temp., max. | 120            |                                  |     |

## Material data

|                           |       |        |        |
|---------------------------|-------|--------|--------|
| Material                  | Wemid | Colour | yellow |
| UL 94 flammability rating | V-0   |        |        |

## System specifications

|         |                   |
|---------|-------------------|
| Version | For the terminals |
|---------|-------------------|

## Additional technical data

|                          |         |                     |                 |
|--------------------------|---------|---------------------|-----------------|
| Explosion-tested version | No      | Installation advice | Direct mounting |
| Type of fixing           | Plugged |                     |                 |

## Cross-connector

|                                     |                 |                           |      |
|-------------------------------------|-----------------|---------------------------|------|
| Number of cross-connected terminals | 4               | Rated current, multi-pole | 10 A |
| Type                                | Cross-connector |                           |      |

## Dimensions

|                 |       |
|-----------------|-------|
| Pitch in mm (P) | 12 mm |
|-----------------|-------|

## General

|                     |                 |                 |   |
|---------------------|-----------------|-----------------|---|
| Installation advice | Direct mounting | Number of poles | 4 |
|---------------------|-----------------|-----------------|---|

## Rating data

|               |      |
|---------------|------|
| Rated current | 24 A |
|---------------|------|

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000489    | ETIM 7.0    | EC000489    |
| ECLASS 9.0  | 27-14-11-40 | ECLASS 9.1  | 27-14-11-40 |
| ECLASS 10.0 | 27-14-11-40 | ECLASS 11.0 | 27-14-11-40 |

## Approvals

Approvals



ROHS

Conform

Creation date March 24, 2021 3:18:33 PM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

## ZQS 2.5/4

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Downloads

Approval/Certificate/Document of  
Conformity

[EAC certificate](#)

Engineering Data

[STEP](#)

Engineering Data

[EPLAN, WSCAD](#)

User Documentation

[StorageConditionsTerminalBlocks](#)