

# LP1N 5.08/03/90 3.2SN OR BX

**Weidmüller Interface GmbH & Co. KG**


Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Product image



Single- and multi-row PCB terminal with proven clamping yoke connection at 5.08 mm pitch, conductor outlet direction 90°. Suitable for conductor cross-sections up to 6.0 mm².

## General ordering data

|              |                                                                                                                                                                               |
|--------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Version      | Printed circuit board terminals, 5.08 mm, Number of poles: 3, 90°, Solder pin length (l): 3.2 mm, tinned, orange, Clamping yoke connection, Clamping range, max. : 6 mm², Box |
| Order No.    | <a href="#">1640840000</a>                                                                                                                                                    |
| Type         | LP1N 5.08/03/90 3.2SN OR BX                                                                                                                                                   |
| GTIN (EAN)   | 4008 190449926                                                                                                                                                                |
| Qty.         | 100 pc(s).                                                                                                                                                                    |
| Product data | IEC: 500 V / 32 A / 0.5 - 6 mm²<br>UL: 300 V / 20 A / AWG 26 - AWG 12                                                                                                         |
| Packaging    | Box                                                                                                                                                                           |

Delivery status: **This article will no longer be available in the future.**

Creation date March 24, 2021 4:51:42 PM CET

Available until 2020-12-31

Alternative product [1975370000](#)

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

## LP1N 5.08/03/90 3.2SN OR BX

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|                          |          |                 |            |
|--------------------------|----------|-----------------|------------|
| Depth                    | 11.5 mm  | Depth (inches)  | 0.453 inch |
| Height                   | 34.2 mm  | Height (inches) | 1.346 inch |
| Height of lowest version | 31 mm    | Net weight      | 6.33 g     |
| Width                    | 15.84 mm | Width (inches)  | 0.624 inch |

## System parameters

|                                              |                             |                                            |                          |
|----------------------------------------------|-----------------------------|--------------------------------------------|--------------------------|
| Product family                               | OMNIMATE Signal - series LP | Wire connection method                     | Clamping yoke connection |
| Mounting onto the PCB                        | THT solder connection       | Conductor outlet direction                 | 90°                      |
| Pitch in mm (P)                              | 5.08 mm                     | Pitch in inches (P)                        | 0.2 inch                 |
| Number of poles                              | 3                           | Pin series quantity                        | 1                        |
| Fitted by customer                           | Yes                         | Max. adjacent poles per row                | 24                       |
| Solder pin length (l)                        | 3.2 mm                      | Solder pin dimensions                      | 0.75 x 0.9 mm            |
| Solder eyelet hole diameter (D)              | 1.3 mm                      | Solder eyelet hole diameter tolerance (D)+ | 0, 1 mm                  |
| Number of solder pins per pole               | 1                           | Screwdriver blade                          | 0.6 x 3.5                |
| Screwdriver blade standard                   | DIN 5264                    | Tightening torque, min.                    | 0.5 Nm                   |
| Tightening torque, max.                      | 0.6 Nm                      | Clamping screw                             | M 3                      |
| Stripping length                             | 6 mm                        | L1 in mm                                   | 10.16 mm                 |
| L1 in inches                                 | 0.4 inch                    | Touch-safe protection acc. to DIN VDE 0470 | IP 20                    |
| Touch-safe protection acc. to DIN VDE 57 106 | Safe from finger touch      | Volume resistance                          | 1.20 mΩ                  |

## Material data

|                                       |                           |                                       |        |
|---------------------------------------|---------------------------|---------------------------------------|--------|
| Insulating material                   | PA                        | Colour                                | orange |
| Colour chart (similar)                | RAL 2000                  | Insulating material group             | I      |
| Comparative Tracking Index (CTI)      | ≥ 600                     | UL 94 flammability rating             | V-2    |
| Contact material                      | Copper alloy              | Contact surface                       | tinned |
| Coating                               | 1-3 µm Ni, 4-6 µm SN      | Tinning type                          | matt   |
| Layer structure of solder connection  | 4...6 µm Ni / 4...6 µm Sn | Storage temperature, min.             | -40 °C |
| Storage temperature, max.             | 70 °C                     | Operating temperature, min.           | -50 °C |
| Operating temperature, max.           | 100 °C                    | Temperature range, installation, min. | -25 °C |
| Temperature range, installation, max. | 100 °C                    |                                       |        |

## Conductors suitable for connection

|                                                 |                         |                                                 |                                                                                                                                                                        |
|-------------------------------------------------|-------------------------|-------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Clamping range, min.                            | 0.13 mm <sup>2</sup>    | Clamping range, max.                            | 6 mm <sup>2</sup>                                                                                                                                                      |
| Wire connection cross section AWG, min.         | AWG 26                  | Wire connection cross section AWG, max.         | AWG 12                                                                                                                                                                 |
| Solid, min. H05(07) V-U                         | 0.5 mm <sup>2</sup>     | Solid, max. H05(07) V-U                         | 6 mm <sup>2</sup>                                                                                                                                                      |
| Flexible, min. H05(07) V-K                      | 0.5 mm <sup>2</sup>     | Flexible, max. H05(07) V-K                      | 4 mm <sup>2</sup>                                                                                                                                                      |
| w. plastic collar ferrule, DIN 46228 pt 4, min. | 0.5 mm <sup>2</sup>     | w. plastic collar ferrule, DIN 46228 pt 4, max. | 2.5 mm <sup>2</sup>                                                                                                                                                    |
| w. wire end ferrule, DIN 46228 pt 1, min.       | 0.5 mm <sup>2</sup>     | w. wire end ferrule, DIN 46228 pt 1, max.       | 2.5 mm <sup>2</sup>                                                                                                                                                    |
| Plug gauge in accordance with EN 60999 a x b; ø |                         | Reference text                                  | Length of ferrules is to be chosen depending on the product and the rated voltage., The outside diameter of the plastic collar should not be larger than the pitch (P) |
|                                                 | 2.8 mm x 2.4 mm; 3.0 mm |                                                 |                                                                                                                                                                        |

## LP1N 5.08/03/90 3.2SN OR BX

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Rated data acc. to IEC

tested acc. to standard

IEC 60664-1, IEC 61984

Rated current, max. number of poles  
(Tu=20°C)

28 A

Rated current, max. number of poles  
(Tu=40°C)

24 A

Rated voltage for surge voltage class /  
pollution degree III/2

250 V

Rated impulse voltage for surge voltage  
class/ pollution degree II/2

4 kV

Rated impulse voltage for surge voltage  
class/ contamination degree III/3

4 kV

Rated current, min. number of poles  
(Tu=20°C)

32 A

Rated current, min. number of poles  
(Tu=40°C)

32 A

Rated voltage for surge voltage class /  
pollution degree II/2

500 V

Rated voltage for surge voltage class /  
pollution degree III/3

250 V

Rated impulse voltage for surge voltage  
class/ pollution degree III/2

4 kV

Short-time withstand current resistance

3 x 1s with 120 A

## Rated data acc. to CSA

Institute (CSA)



Certificate No. (CSA)

200039-1202191

Rated voltage (Use group B / CSA)

300 V

Rated current (Use group B / CSA)

20 A

Wire cross-section, AWG, min.

AWG 26

Reference to approval values

Specifications are  
maximum values, details -  
see approval certificate.

Rated voltage (Use group D / CSA)

300 V

Rated current (Use group D / CSA)

10 A

Wire cross-section, AWG, max.

AWG 12

## Rated data acc. to UL 1059

Institute (UR)



Certificate No. (UR)

E60693

Rated voltage (Use group B / UL 1059)

300 V

Rated current (Use group B / UL 1059)

20 A

Wire cross-section, AWG, min.

AWG 26

Reference to approval values

Specifications are  
maximum values, details -  
see approval certificate.

Rated voltage (Use group D / UL 1059)

300 V

Rated current (Use group D / UL 1059)

10 A

Wire cross-section, AWG, max.

AWG 12

## Packing

Packaging

Box

VPE length

84 mm

VPE width

117 mm

VPE height

168 mm

## Classifications

ETIM 6.0

EC002643

ETIM 7.0

EC002643

ECLASS 9.0

27-44-04-01

ECLASS 9.1

27-44-04-01

ECLASS 10.0

27-44-04-01

ECLASS 11.0

27-46-01-01

## LP1N 5.08/03/90 3.2SN OR BX

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Important note

|                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| IPC conformity | Conformity: The products are developed, manufactured and delivered according international recognized standards and norms and comply with the assured properties in the data sheet resp. fulfill decorative properties in accordance with IPC-A-610 "Class 2". Further claims on the products can be evaluated on request.                                                                                                                                                                                                                                                                                                                     |
| Notes          | <ul style="list-style-type: none"> <li>• Additional colours on request</li> <li>• Rated current related to rated cross-section &amp; min. No. of poles.</li> <li>• Wire end ferrule without plastic collar to DIN 46228/1</li> <li>• Wire end ferrule with plastic collar to DIN 46228/4</li> <li>• P on drawing = pitch</li> <li>• Rated data refer only to the component itself. Clearance and creepage distances to other components are to be designed in accordance with the relevant application standards.</li> <li>• Long term storage of the product with average temperature of 50 °C and average humidity 70%, 36 months</li> </ul> |

### Approvals

Approvals



|                       |         |
|-----------------------|---------|
| ROHS                  | Conform |
| UL File Number Search | E60693  |

### Downloads

|                                             |                                                 |
|---------------------------------------------|-------------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">Declaration of the Manufacturer</a> |
| Engineering Data                            | <a href="#">EPLAN, WSCAD</a>                    |


## LP1N 5.08/03/90 3.2SN OR BX

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany


[www.weidmueller.com](http://www.weidmueller.com)

# Drawings

## Dimensional drawing







## Graph



**WEIDMUELLER INTERFACE GmbH & Co.KG**

SCREWDRIVER



SHOWN: LP1N 5.08/04/90...

Weidmüller PCB components are tested to the DIN EN 61984 standard, and are valid for its field of application. Provided that the components are used to the intended purpose, all requirements with respect to the occurring of electrical, mechanical, thermic and corrosive stress will be satisfied.

|          |                |                  |
|----------|----------------|------------------|
| 24       | 116,84         | 4,600            |
| 23       | 111,76         | 4,400            |
| 22       | 106,68         | 4,200            |
| 21       | 101,60         | 4,000            |
| 20       | 96,52          | 3,800            |
| 19       | 91,44          | 3,600            |
| 18       | 86,36          | 3,400            |
| 17       | 81,28          | 3,200            |
| 16       | 76,20          | 3,000            |
| 15       | 71,12          | 2,800            |
| 14       | 66,04          | 2,600            |
| 13       | 60,96          | 2,400            |
| 12       | 55,88          | 2,200            |
| 11       | 50,80          | 2,000            |
| 10       | 45,72          | 1,800            |
| 9        | 40,64          | 1,600            |
| 8        | 35,56          | 1,400            |
| 7        | 30,48          | 1,200            |
| 6        | 25,40          | 1,000            |
| 5        | 20,32          | 0,800            |
| 4        | 15,24          | 0,600            |
| 3        | 10,16          | 0,400            |
| 2        | 5,08           | 0,200            |
| <b>n</b> | <b>L1 [mm]</b> | <b>L1 [Inch]</b> |

|                                                                                                                                                                  |                            |            |           |                                                                                                            |                |  |              |      |   |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|------------|-----------|------------------------------------------------------------------------------------------------------------|----------------|--|--------------|------|---|
|  <div>METRIC TOLERANCES<br/>X. = ±0.3<br/>X.X = ±0.1<br/>X.XX = ±0.05</div> | 59484/0<br>22.07.11 KRUG_M |            | 01        | <div>Weidmüller</div> | CAT.NO.: . . . |  | C 21227      | 13   |   |
|                                                                                                                                                                  | MODIFICATION               |            |           |                                                                                                            | DRAWING NO.    |  | ISSUE NO.    |      |   |
|                                                                                                                                                                  |                            |            |           |                                                                                                            | SHEET 01       |  | OF 01 SHEETS |      |   |
|                                                                             |                            | DATE       | NAME      | <div>LP1N 5.08/.../90...<br/>LEITERPLATTENKLEMME<br/>PCB-TERMINAL</div>                                    |                |  |              |      |   |
|                                                                                                                                                                  | DRAWN                      | 11.05.2009 | HELIS_MA  |                                                                                                            |                |  |              |      |   |
|                                                                                                                                                                  | RESPONSIBLE                |            | KRUG_M    |                                                                                                            |                |  |              |      |   |
| SCALE: 2/1                                                                                                                                                       | CHECKED                    | 25.07.2011 | HECKERT_M |                                                                                                            |                |  |              |      |   |
| SUPERSEDES: .                                                                                                                                                    | APPROVED                   |            | HECKERT_M | PRODUCT FILE: LP2N(2H 3R)                                                                                  |                |  |              | 7361 | ▪ |

## Recommended wave soldering profiles

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

### Single Wave:



### Double Wave:



### Wave soldering profiles

Wired connection elements should be processed in accordance with the DIN EN 61760-1 standard. We have included two recommendations for practical wave soldering profiles, with which Weidmüller PCB terminals and connectors are qualified.

When choosing a suitable profile for your application, the following factors also need to be considered:

- PCB thickness
- Proportion of Cu in the layers
- Single/double-sided assembly
- Product range
- Heating and cooling rates

The single and double wave profiles each indicate the recommended operating range, including the maximum soldering temperature of 260°C. In practice, the maximum soldering temperature is quite often well below the above maximum profile.

We reserve the right to make technical changes.