



# Flat cylinder DZH-32- -PPV-A-S6

Part number: 16531

FESTO



General operating condition

## Data sheet

Overall data sheet – Individual values depend upon your configuration.

| Feature                                      | Value                                                              |
|----------------------------------------------|--------------------------------------------------------------------|
| Stroke                                       | 1 mm ... 1000 mm                                                   |
| Piston diameter                              | 32 mm<br>Equivalent diameter                                       |
| Piston rod thread                            | M10x1.25                                                           |
| Max. angle of rotation of the piston rod +/- | 1.7 deg                                                            |
| Cushioning                                   | Pneumatic cushioning, adjustable at both ends                      |
| Mounting position                            | Any                                                                |
| Mode of operation                            | Double-acting                                                      |
| Structural design                            | Piston<br>Piston rod                                               |
| Position sensing                             | For proximity sensor                                               |
| Symbol                                       | 00991235                                                           |
| Variants                                     | Heat-resistant seals max. 120°C                                    |
| Protection against torsion/guide             | Oval piston                                                        |
| Operating pressure                           | 0.06 MPa ... 1 MPa                                                 |
| Operating pressure                           | 0.6 bar ... 10 bar                                                 |
| Operating medium                             | Compressed air as per ISO 8573-1:2010 [7:4:4]                      |
| Information on operating and pilot media     | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC)             | 2 - Moderate corrosion stress                                      |
| LABS (PWIS) conformity                       | VDMA24364-B2-L                                                     |
| Ambient temperature                          | 0 °C ... 120 °C                                                    |
| Cushioning length                            | 19 mm                                                              |
| Max. torque for protection against rotation  | 1 Nm                                                               |
| Theoretical force at 6 bar, retracting       | 415 N                                                              |
| Theoretical force at 6 bar, advancing        | 483 N                                                              |
| Moving mass at 0 mm stroke                   | 143 g                                                              |
| Additional moving mass per 10 mm stroke      | 8.9 g                                                              |
| Additional weight per 10 mm stroke           | 25 g                                                               |
| Basic weight with 0 mm stroke                | 528 g                                                              |
| Type of mounting                             | With internal thread<br>With accessories                           |
| Pneumatic connection                         | G1/8                                                               |
| Note on materials                            | RoHS-compliant                                                     |
| Cover material                               | Aluminum                                                           |
| Seals material                               | FPM                                                                |

| Feature              | Value            |
|----------------------|------------------|
| Housing material     | Aluminum         |
| Piston seal material | FPM              |
| Piston rod material  | High-alloy steel |