

**HDC 24D TSBO 1PG16G****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

**General ordering data**

|            |                                                                                                                                                                                    |
|------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Version    | HDC enclosures, Size: 4, Protection degree: IP65 (in plugged condition), Cable entry from side, Plug housing, Side-locking clamp on upper side, high, Size of cable entries: PG 16 |
| Order No.  | <a href="#">1654810000</a>                                                                                                                                                         |
| Type       | HDC 24D TSBO 1PG16G                                                                                                                                                                |
| GTIN (EAN) | 4008190407810                                                                                                                                                                      |
| Qty.       | 1 pc(s).                                                                                                                                                                           |

## HDC 24D TSO 1PG16G

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|                |            |                 |            |
|----------------|------------|-----------------|------------|
| Height         | 72 mm      | Height (inches) | 2.835 inch |
| Net weight     | 252 g      | Width           | 55 mm      |
| Width (inches) | 2.165 inch |                 |            |

## Temperatures

|                   |                   |
|-------------------|-------------------|
| Limit temperature | -40 °C ... 125 °C |
|-------------------|-------------------|

## Environmental Product Compliance

|                     |                                                                |                         |
|---------------------|----------------------------------------------------------------|-------------------------|
| REACH SVHC          | Lead 7439-92-1, Potassium perfluorobutane sulfonate 29420-49-3 |                         |
| Chemical resistance | Substance                                                      | Acetone                 |
|                     | Chemical resistance                                            | Conditionally resistant |
|                     | Substance                                                      | Drilling oil            |
|                     | Chemical resistance                                            | Resistant               |
|                     | Substance                                                      | Diesel                  |
|                     | Chemical resistance                                            | Resistant               |
|                     | Substance                                                      | Ethyl alcohol           |
|                     | Chemical resistance                                            | Resistant               |
|                     | Substance                                                      | Transmission oil        |
|                     | Chemical resistance                                            | Resistant               |
|                     | Substance                                                      | Hydraulic oil           |
|                     | Chemical resistance                                            | Resistant               |
|                     | Substance                                                      | Coolant                 |
|                     | Chemical resistance                                            | Resistant               |
|                     | Substance                                                      | Petroleum benzine       |
|                     | Chemical resistance                                            | Resistant               |
|                     | Substance                                                      | Sweat                   |
|                     | Chemical resistance                                            | Resistant               |
|                     | Substance                                                      | Premium gasoline        |
|                     | Chemical resistance                                            | Conditionally resistant |
|                     | Substance                                                      | Water                   |
|                     | Chemical resistance                                            | Resistant               |
|                     | Substance                                                      | UV                      |
|                     | Chemical resistance                                            | Unstable                |
|                     | Substance                                                      | Ozone                   |
|                     | Chemical resistance                                            | Unstable                |

## Dimensions

|                      |              |                     |       |
|----------------------|--------------|---------------------|-------|
| Cable entry          | w. threading | Height of housing B | 72 mm |
| Total length housing | 73 mm        | Width housing C     | 43 mm |

## General data

|                             |                             |                       |                             |
|-----------------------------|-----------------------------|-----------------------|-----------------------------|
| EMC housings                | No                          | Housing main material | diecast aluminium           |
| Material of locking element | Stainless steel, rust-proof | Protection degree     | IP65 (in plugged condition) |
| Surface finish              | Powder coating              | Tightening torque     | 1.2 Nm                      |

## HDC 24D TSBO 1PG16G

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Version

|                              |                                  |                                |                                     |
|------------------------------|----------------------------------|--------------------------------|-------------------------------------|
| Cable entry                  | w. threading                     | Clamp version                  | Side-locking clamp                  |
| Design                       | high                             | Design of housing              | Cable entry from side, Plug housing |
| Design of locking system     | Side-locking clamp on upper side | Internal thread                | PG 16                               |
| Number of cable entry on top | 0                                | Number of cable entry sideways | 1                                   |
| Size                         | 4                                | Size of cable entries          | PG 16                               |
| Suitable for ModuPlug®       | Yes                              | Tightening torque              | 1.2 Nm                              |
| Top part/bottom part/lid     | upper part                       | Type                           | Plug                                |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000437    | ETIM 7.0    | EC000437    |
| ECLASS 9.0  | 27-44-02-02 | ECLASS 9.1  | 27-44-02-02 |
| ECLASS 10.0 | 27-44-02-02 | ECLASS 11.0 | 27-44-02-02 |

## Approvals

Approvals



ROHS

Conform

## Downloads

|                                             |                                                                |
|---------------------------------------------|----------------------------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">Manufacturer's declaration</a>                     |
| Engineering Data                            | <a href="#">STEP</a>                                           |
| Engineering Data                            | <a href="#">EPLAN, WSCAD</a>                                   |
| Technical Documentation                     | <a href="#">1654810000 HDC 24D TSBO 1PG16G STP Blatt 1.pdf</a> |

### HDC 24D TSB0 1PG16G

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

