

**RD 16/11****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Similar to illustration**

In addition to cable glands for a wide range of applications, the product portfolio is rounded off by plugs, pressure compensation elements, adaptors and the corresponding accessories such as locknuts, sealing rings, flat washers and earthing rings.

**General ordering data**

|            |                                                                |
|------------|----------------------------------------------------------------|
| Version    | Gauge rings, Adapter, PG 16 ,PG 11, IP54, Brass, nickel-plated |
| Order No.  | <a href="#">1656110000</a>                                     |
| Type       | RD 16/11                                                       |
| GTIN (EAN) | 4008190409128                                                  |
| Qty.       | 50 pc(s).                                                      |

**RD 16/11****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|            |       |
|------------|-------|
| Net weight | 9.8 g |
|------------|-------|

**Environmental Product Compliance**

|            |                |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

**General information**

|                                   |                      |                                   |                                                                          |
|-----------------------------------|----------------------|-----------------------------------|--------------------------------------------------------------------------|
| External thread                   | PG 16                | Internal thread                   | PG 11                                                                    |
| Material                          | Brass, nickel-plated | Note: protection class            | Please follow the operating instructions to attain higher IP protection. |
| Operating temperature range, max. | 100 °C               | Operating temperature range, min. | -40 °C                                                                   |
| Protection degree                 | IP54                 | Protection degree with GWDR       | IP54                                                                     |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000441    | ETIM 7.0    | EC000441    |
| ECLASS 9.0  | 27-14-44-14 | ECLASS 9.1  | 27-14-44-90 |
| ECLASS 10.0 | 27-14-44-14 | ECLASS 11.0 | 27-14-44-14 |

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                  |                              |
|------------------|------------------------------|
| Engineering Data | <a href="#">WSCAD, EPLAN</a> |
|------------------|------------------------------|