



Main

Range of product	DuoLine
Product name	DuoLine MIN'clac
Device short name	MIN'clac
Product or component type	Electromechanical timer
Colour tint	White (RAL 9003)

Complementary

Device application	Residential
Load type	230 V AC halogen lamp (2300 W) 230 V AC incandescent lamp (2300 W) non-corrected fluorescent tube (2300 W) parallel-corrected fluorescent tube (1300 VA) serial-corrected fluorescent tube (2300 W)
Maximum power consumption in VA	1 VA
Maximum switching current	16 A - 230 V AC pf = 1
[Ue] rated operational voltage	230 V AC $\pm 10\%$ at 50/60 Hz
Time delay	Adjustable from 1 to 7 minutes
Mounting support	DIN rail
9 mm pitches	2
Connections - terminals	Screw terminals - $\leq 6 \text{ mm}^2$
Product weight	84 g

Environment

Ambient air temperature for operation	-10...50 °C
IP degree of protection	IP20

Offer Sustainability

Sustainable offer status	Green Premium product
--------------------------	-----------------------

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	18 months
----------	-----------