

HDC-C-M20-SCG0.2-0.52AU**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Crimps provide a electrical and mechanical connection between wire and contact that is both secure and reliable. The optimal crimp connection is gas-tight and corrosion-resistant.

General ordering data

Version	Heavy-duty connectors, Crimp contact, CM 20, Pin, Conductor cross-section, max.: 0.52, punched, Copper alloy
Order No.	1682440000
Type	HDC-C-M20-SCG0.2-0.52AU
GTIN (EAN)	4008190859947
Qty.	500 pc(s).

HDC-C-M20-SCG0.2-0.52AU**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Technical data****Dimensions and weights**

Net weight	0.232 g
------------	---------

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

General data

Conductor cross-section, max.	0.52 mm ²	Conductor cross-section, min.	0.2 mm ²
Contact diameter, male Ø	1 mm	Cross-section for connected wire	0.2 - 0.52 mm ²
Material	Copper alloy	Production methods	punched
Stripping length, rated connection	2.5 mm	Surface finish	gold
Type	Pin	Type of connection	Crimp connection
Version insert	CM 20	Volume resistance	≤5 mΩ

Classifications

ETIM 6.0	EC000796	ETIM 7.0	EC000796
ECLASS 9.0	27-44-02-04	ECLASS 9.1	27-44-02-04
ECLASS 10.0	27-44-02-04	ECLASS 11.0	27-44-02-04

Approvals

Approvals



ROHS	Conform
------	---------

Downloads

Engineering Data	WSCAD
------------------	-----------------------

HDC-C-M20-SCG0.2-0.52AU

Weidmüller Interface GmbH & Co. KG


Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Drawings



Leiterquerschnitt

Abisolierlänge

0,08 - 0,20 mm² AWG 28-24 2,5+0,5 mm

0,20 - 0,52 mm² AWG 24-20 2,5+0,5 mm

