

LM WO 23/55 WS**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Self-adhesive polyester labels which are suitable for A4 office laser printer.

General ordering data

Version	LaserMark, Conductor and cable markers, 6.8 - 12 mm, {Reference (AttributeDefinition) not found: pAttr74196859207437}, white
Order No.	1695721044
Type	LM WO 23/55 WS
GTIN (EAN)	4008190924676
Qty.	10 pc(s).

LM WO 23/55 WS

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	0.025 mm	Depth (inches)	0.001 inch
Height	23 mm	Height (inches)	0.906 inch
Net weight	10.1 g	Width	55 mm
Width (inches)	2.165 inch		

Temperatures

Operating temperature range	-40...150 °C
-----------------------------	--------------

General data

Adhesive	Acrylate	Colour	white
Halogen	No	Material	Polyester film
Material colour according to resistance code	9	Number of markers per combination	1 Label sheet = 40 Conductor and cable markers
Number per sheet	40	Operating temperature range	-40...150 °C
Operating temperature range, max.	150 °C	Operating temperature range, min.	-40 °C
Size of labelling field	23 x 12.7 mm	Type of printing	neutral
UL 94 flammability rating	V-0	Version	Self-adhesive
Width	55 mm		

Conductor and cable markers

Conductor O.D.	6.8 - 12 mm	Conductor O.D., max.	12 mm
Conductor O.D., min.	6.8 mm	Conductor cross-section, max.	50 mm ²
Conductor cross-section, min.	10 mm ²	Cross-section for connected wire	10 - 50 mm ²
Halogen	No	Text field height	12.5 mm
Text field width	22.8 mm		

Classifications

ETIM 6.0	EC001530	ETIM 7.0	EC001530
ECLASS 9.0	27-40-04-01	ECLASS 9.1	27-40-04-01
ECLASS 10.0	27-40-04-01	ECLASS 11.0	27-28-11-02

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	STEP
Engineering Data	EPLAN, WSCAD, Zuken E3.S

LM WO 23/55 WS

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

