

## MARKO-C. 25X25X25 B/DR.

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)



### General ordering data

Version	Device markers, Device markers, {Reference (AttributeDefinition) not found: pAttr74196859207437}, yellow
Order No.	<a href="#">1700530001</a>
Type	MARKO-C. 25X25X25 B/DR.
GTIN (EAN)	4008190896195
Qty.	10 pc(s).

Creation date March 24, 2021 8:48:24 PM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

**MARKO-C. 25X25X25 B/DR.****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

Depth	0.05 mm	Depth (inches)	0.002 inch
Height	25 mm	Height (inches)	0.984 inch
Net weight	2.6 g	Width	25 mm
Width (inches)	0.984 inch		

**Temperatures**

Operating temperature range	-29...80 °C
-----------------------------	-------------

**General data**

Adhesive	Permanent acrylic copolymer	Colour	yellow
Colour of printing	black	Material	Acrylic-coated fibre webbing
Material colour according to resistance code	4	Number of markers per combination	1 Label sheet = 14 Device markers
Operating temperature range	-29...80 °C	Operating temperature range, max.	80 °C
Operating temperature range, min.	-29 °C	Printed characters	Symbols
Printing	Lightning flash in triangle	Version	Self-adhesive
Width	25 mm		

**Classifications**

ETIM 6.0	EC001288	ETIM 7.0	EC001288
ECLASS 9.0	27-40-06-29	ECLASS 9.1	27-40-06-29
ECLASS 10.0	27-40-06-29	ECLASS 11.0	27-28-11-04

**Approvals**

ROHS	Conform
------	---------

**Downloads**

Engineering Data	<a href="#">EPLAN, WSCAD</a>
------------------	------------------------------

**Data sheet**

**MARKO-C. 25X25X25 B/DR.**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

