

# Product data sheet

## Characteristics

# 170BNO67100

branch interface - for Interbus communication adaptor - 24 V DC

### Main

Range of product	Modicon Momentum automation platform
Accessory / separate part designation	Branch interface
Accessory / separate part type	Interface
Accessory / separate part category	Connection accessories
Accessory / separate part destination	Interbus communication adaptor
Communication port protocol	Interbus generation SUPI 2

### Complementary

[Us] rated supply voltage	24 V DC
Output current limits	0.2...2 A
Power dissipation in W	2.5 W
Current consumption	100 mA
Electrical connection	1 terminal block 8 1 RS485 connector RJ45 for outgoing remote bus 1 RS485 connector RJ45 for incoming remote bus
Local signalling	1 LED red remote bus disabled (RD) 1 LED red remote bus branch error (E) 1 LED green relay output (REL) 1 LED green ready for operation (ready) 1 LED green local remote bus branch disabled (LD) 1 LED green bus active (BA) 1 LED green remote bus check (RC)
Product weight	0.015 kg

### Environment

Standards	DIN 19258
-----------	-----------

### Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1015 -  Schneider Electric declaration of conformity