

VG 11-MS54-ZE**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Similar to illustration**

In addition to the extensive range of enclosures, Weidmüller offers a variety of cable glands for a wide range of applications.

The cable glands made of brass, plastic and stainless steel meet the most various IP protection classes to suit any industrial enclosure.

Depending on the series of cable glands and the application, the cable glands are approved and tested according to VDE, UL, UR, cULus, DNV GL or EN 45545.

General ordering data

Version	VG MS ZE (standard brass cable gland strain relief), Cable glands, PG 11, 6 mm, OD min. 6.5 - OD max. 12.5 mm, IP65, Brass, nickel-plated
Order No.	1718820000
Type	VG 11-MS54-ZE
GTIN (EAN)	4008190352042
Qty.	50 pc(s).

Creation date March 24, 2021 10:25:20 PM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

VG 11-MS54-ZE

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Length	31.5 mm	Length (inches)	1.24 inch
Net weight	40.86 g		

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

General information

AF size 1	22 mm	AF size 2	20 mm
Cable glands	PG	Clamping range, strain relief, max.	12 mm
Clamping range, strain relief, min.	7.5 mm	External thread	PG 11
Halogen	No	Length of thread	6 mm
Material	Brass, nickel-plated	Operating temperature range, max.	80 °C
Operating temperature range, min.	-20 °C	Outer cable diameter, max.	12.5 mm
Outer cable diameter, min.	6.5 mm	Protection degree	IP54
Protection degree with GWDR	IP65	Seal insert	NBR
Torque for cap nut, max.	4.2 Nm	Torque for cap nut, min.	4.2 Nm
Torque for connecting adapter, max.	6.25 Nm	Torque for connecting adapter, min.	6.25 Nm

Classifications

ETIM 6.0	EC000441	ETIM 7.0	EC000441
ECLASS 9.0	27-14-44-32	ECLASS 9.1	27-14-44-32
ECLASS 10.0	27-14-44-32	ECLASS 11.0	27-14-44-32

Approvals

Approvals



ROHS	Conform
------	---------

Downloads

Engineering Data	EPLAN, WSCAD
------------------	------------------------------