

**CB 290/3.5 BLACK****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

CB cable ties for the fastening of cables and markers.

- They are particularly suitable for fastening CLI M, SFX, WKM and WKS cable markers
- IEC 62275: 2006-conformant
- Fracture-resistant polyamide PA 6.6 with flammability rating V2 to UL-94

**General ordering data**

|            |                                                                                                                                                                     |
|------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Version    | Cable ties, {Reference (AttributeDefinition) not found: pAttr74196859207437}: {Reference (AttributeDefinition) not found: pAttr74196859207437}, Polyamide 66, 130 N |
| Order No.  | <a href="#">1720650000</a>                                                                                                                                          |
| Type       | CB 290/3.5 BLACK                                                                                                                                                    |
| GTIN (EAN) | 4008190362331                                                                                                                                                       |
| Qty.       | 100 pc(s).                                                                                                                                                          |

Creation date March 24, 2021 10:35:35 PM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

**CB 290/3.5 BLACK****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|                |            |                 |             |
|----------------|------------|-----------------|-------------|
| Depth          | 1.2 mm     | Depth (inches)  | 0.047 inch  |
| Height         | 290 mm     | Height (inches) | 11.417 inch |
| Net weight     | 1.36 g     | Width           | 3.6 mm      |
| Width (inches) | 0.142 inch |                 |             |

**Temperatures**

|                             |             |
|-----------------------------|-------------|
| Operating temperature range | -40...85 °C |
|-----------------------------|-------------|

**Installation materials**

|                                   |       |                                   |              |
|-----------------------------------|-------|-----------------------------------|--------------|
| Cable diameter, max.              | 80 mm | For re-opening                    | No           |
| Halogen                           | No    | Material                          | Polyamide 66 |
| Operating temperature range, max. | 85 °C | Operating temperature range, min. | -40 °C       |
| Tensile strength                  | 130 N | UL 94 flammability rating         | V-2          |
| UV-resistant                      | No    |                                   |              |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000046    | ETIM 7.0    | EC000046    |
| ECLASS 9.0  | 27-14-07-02 | ECLASS 9.1  | 27-14-07-02 |
| ECLASS 10.0 | 27-14-07-02 | ECLASS 11.0 | 27-14-07-02 |

**Approvals**

Approvals



|                       |         |
|-----------------------|---------|
| ROHS                  | Conform |
| UL File Number Search | E317499 |

**Downloads**

|                                             |                                        |
|---------------------------------------------|----------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">DE PI830000 160627 001</a> |
| Engineering Data                            | <a href="#">EPLAN, WSCAD</a>           |

### CB 290/3.5 BLACK

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

