

KSP L30**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Similar to illustration

In addition to cable glands for a wide range of applications, the product portfolio is rounded off by plugs, pressure compensation elements, adaptors and the corresponding accessories such as locknuts, sealing rings, flat washers and earthing rings.

General ordering data

Version	KSP (Klippon shroud), Protective cap, PVC
Order No.	1736580000
Type	KSP L30
GTIN (EAN)	4008 1909 56233
Qty.	10 pc(s).

KSP L30**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Length	130 mm	Length (inches)	5.118 inch
Net weight	26 g	Wall thickness, max.	2 mm
Wall thickness, min.	2 mm		

General information

Gap, internal dimension B	75 mm	Hardness (Shore A)	65
Inside diameter D2	30 mm	Material	PVC
O.D.	34 mm	Operating temperature range, max.	70 °C
Operating temperature range, min.	-25 °C	Thickness	2 mm

Classifications

ETIM 6.0	EC000441	ETIM 7.0	EC000441
ECLASS 9.0	27-14-44-32	ECLASS 9.1	27-14-44-90
ECLASS 10.0	27-14-44-32	ECLASS 11.0	27-14-44-32

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	STEP
Engineering Data	EPLAN, WSCAD

KSP L30

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

