

**ADAP EX M63-M75****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Similar to illustration**

In addition to cable glands for a wide range of applications, the product portfolio is rounded off by plugs, pressure compensation elements, adaptors and the corresponding accessories such as locknuts, sealing rings, flat washers and earthing rings.

**General ordering data**

|            |                                                                                               |
|------------|-----------------------------------------------------------------------------------------------|
| Version    | ADAP (adaptor, extensions and reductions),<br>Adapter, M 63 ,M 75, IP54, Brass, nickel-plated |
| Order No.  | <a href="#">1738330000</a>                                                                    |
| Type       | ADAP EX M63-M75                                                                               |
| GTIN (EAN) | 4008190958770                                                                                 |
| Qty.       | 1 pc(s).                                                                                      |

**ADAP EX M63-M75****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|            |       |
|------------|-------|
| Net weight | 398 g |
|------------|-------|

**Environmental Product Compliance**

|            |                |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

**Certificate numbers cable gland**

|                                     |                    |                                    |                                   |
|-------------------------------------|--------------------|------------------------------------|-----------------------------------|
| Approval conditions                 | ATEX, IECEX        | Certificate no. cable gland (ATEX) | SIRA 10ATEX1225X                  |
| Certificate no. cable gland (IECEX) | IECEX SIR 07.0010X | Identification                     | II 2 GD, Ex d IIC, Ex e II, Ex tD |

**General information**

|                                   |                                                                          |                                   |                      |
|-----------------------------------|--------------------------------------------------------------------------|-----------------------------------|----------------------|
| Cable glands                      | metric                                                                   | External thread                   | M 63                 |
| Internal thread                   | M 75                                                                     | Material                          | Brass, nickel-plated |
| Note: protection class            | Please follow the operating instructions to attain higher IP protection. | Operating temperature range, max. | 100 °C               |
| Operating temperature range, min. | -40 °C                                                                   | Pitch of thread                   | 1.5                  |
| Protection degree                 | IP54                                                                     | Protection degree with GWDR       | IP54                 |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000441    | ETIM 7.0    | EC000441    |
| ECLASS 9.0  | 27-14-44-32 | ECLASS 9.1  | 27-14-44-90 |
| ECLASS 10.0 | 27-14-44-32 | ECLASS 11.0 | 27-14-44-32 |

**Approvals**

Approvals



|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                  |                              |
|------------------|------------------------------|
| Engineering Data | <a href="#">EPLAN, WSCAD</a> |
|------------------|------------------------------|