

LPZP 1.27/90 OR

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com



The maximum voltage is based on the minimum distance.

Intermediate plates increase the creepage and clearance distances between different potentials and permit higher rated voltages or a clear separation, e.g. between mains and low voltages or different protection zones. The dovetail joint enables easy installation and guarantees a secure fit. Other characteristics include:

- Pitch extended by 1.27 or 2.54mm all other combinations possible
- Colour coding ensures visual differentiation
- Different geometries for standard designs.

Incomplete individual assemblies avoided because separate terminal blocks combine to form a single holistic unit. Ready-assembled on request.

The advantages: efficient processing, increased stability, improved reliability.

General ordering data

Version	Printed circuit board terminals, Accessories,
	Intermediate plate, orange, Number of poles: 1
Order No.	<u>1747490000</u>
Туре	LPZP 1.27/90 OR
GTIN (EAN)	4008190992170
Qty.	100 pc(s).
Product data	
Packaging	Вох



LPZP 1.27/90 OR

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Dimensions	and	l weights
------------	-----	-----------

Net weight	0.2 a

System parameters

Number of poles	1	Pin series quantity	1

Material data

Insulating material	PA	Colour	orange
Colour chart (similar)	RAL 2000	Storage temperature, min.	-40 °C
Storage temperature, max.	70 °C	Operating temperature, min.	-50 °C
Operating temperature, max.	100 °C	Temperature range, installation, min.	-25 °C
Temperature range, installation, max.	100 °C		

Conductors suitable for connection

Reference text	Length of ferrules is to
	be chosen depending
	on the product and the
	roted voltage. The cutoide

on the product and the rated voltage., The outside diameter of the plastic collar should not be larger than the pitch (P)

Rated data acc. to IEC

tested acc to standard	IEC 60664-1 IEC 61984	

Packing

Packaging	Box	VPE length	35 mm
VPE width	35 mm	VPE height	90 mm

Classifications

ETIM 6.0	EC002643	ETIM 7.0	EC002643
ECLASS 9.0	27-44-04-01	ECLASS 9.1	27-44-04-01
ECLASS 10.0	27-44-04-01	ECLASS 11.0	27-46-01-01

Important note

standards and norms and comply with the assured properties in the data sheet resp. fulfill decorative properties
standards and norms and comply with the assured properties in the data sheet resp. fulfill decorative properties
onformity Conformity: The products are developed, manufactured and delivered according international recognized

Notes • Long term storage of the product with average temperature of 50 °C and average humidity 70%, 36 months

Approvals

Approvals



ROHS Conform



LPZP 1.27/90 OR

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Downloads

Approval/Certificate/Document of Conformity

Declaration of the Manufacturer