Weidmüller

BS 35II KLBUE3-8/2X2-6

Product image

Shielding and earthing

Our protective earth conductor and shielding terminals featuring different connection technologies allow you to effectively protect both people and equipment from interference, such as electrical or magnetic fields. A comprehensive range of accessories rounds off our range.

General ordering data

Version	Clamping yoke, Set of fixings, Steel
Order No.	1749430000
Type	BS 35II KLBUE3-8/2X2-6
GTIN (EAN)	4032248013210
Qty.	10 pc(s).

BS 35II KLBUE3-8/2X2-6

Technical data

Dimensions and weights

Depth	36.5 mm	Depth (inches)	1.437 inch
Diameter	3 mm	Height	35 mm
Height (inches)	1.378 inch	Net weight	60.8 g

Temperatures

Storage temperature	-25 °C...55 °C

Material data

Material	Steel	Colour	silver

System specifications

Version	Clamping yoke	Rail	TS 35

Additional technical data

Explosion-tested version	Yes	Installation advice	Direct mounting
Type of fixing	when screwed in		

Conductors for clamping (rated connection)

Cable diameter, max.	8 mm	Cable diameter, min.	3 mm

Dimensions

Diameter	3 mm	TS 35 offset	26.5 mm

General

Installation advice	Direct mounting	Rail	TS 35

Classifications

ETIM 6.0	EC002848	ETIM 7.0	EC002848
ECLASS 9.0	27-14-11-92	ECLASS 9.1	27-14-11-92
ECLASS 10.0	27-14-11-92	ECLASS 11.0	27-14-11-92

Approvals

ROHS	Conform

Downloads

Engineering Data	STEP
Engineering Data	EPLAN, WSCAD
User Documentation	Beipackzettel_KLBUE.pdf
	StorageConditionsTerminalBlocks