

THM WO 25/140 WS**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



Similar to illustration

THM WriteOn cable markers on reels are used for labelling conductors and cables with an outside diameter of up to 36 mm. The transparent adhesive strip fixes and protects the printing on the marker surface.

- Protection of the marking against dirt and abrasion by wrapping it with the transparent adhesive strip
- Simple and quick printing with the high-quality thermal transfer printers

General ordering data

Version	THM, Conductor and cable markers, 8.3 - 36.4 mm, {Reference (AttributeDefinition) not found: pAttr74196859207437}, white
Order No.	1751561044
Type	THM WO 25/140 WS
GTIN (EAN)	4032248001040
Qty.	1 pc(s).
compatible printer	2599430000 2599440000

Creation date March 25, 2021 2:37:16 AM CET

THM WO 25/140 WS

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	0.025 mm	Depth (inches)	0.001 inch
Height	25 mm	Height (inches)	0.984 inch
Net weight	645 g	Width	140 mm
Width (inches)	5.512 inch		

Temperatures

Operating temperature range	-40...150 °C
-----------------------------	--------------

General data

Adhesive	Polyacrylate adhesive	Approval acc. to UL 969	Yes
Colour	white	Halogen	No
Material	Polyester film	Material colour according to resistance code	9
Number of markers per combination	1 Label reel = Conductor and cable markers	Number per roll	1,050
Operating temperature range	-40...150 °C	Operating temperature range, max.	150 °C
Operating temperature range, min.	-40 °C	Size of labelling field	26 x 25 mm
Type of printing	neutral	UL 94 flammability rating	V-0
Version	Self-adhesive	Width	140 mm

Conductor and cable markers

Conductor O.D.	8.3 - 36.4 mm	Conductor O.D., max.	36.4 mm
Conductor O.D., min.	8.3 mm	Conductor cross-section, max.	500 mm ²
Conductor cross-section, min.	0.75 mm ²	Cross-section for connected wire	0.75 - 500 mm ²
Halogen	No	Text field height	26 mm
Text field width	25 mm		

Classifications

ETIM 6.0	EC001530	ETIM 7.0	EC001530
ECLASS 9.0	27-40-04-01	ECLASS 9.1	27-40-04-01
ECLASS 10.0	27-40-04-01	ECLASS 11.0	27-28-11-02

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	STEP
Engineering Data	EPLAN, WSCAD, Zuken E3.S

Data sheet

THM WO 25/140 WS

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

