

SAI 4/6/8 MH-MHD BLZF**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Cable gland: M25 for cables with an outer insulation diameter from 13 mm to 18 mm. The SAI distributor with M25 cable gland is suitable among others for the following cable types:

- 21 x 0.50 mm
- 18 x 0.75 mm bis 21 x 0.75 mm
- 14 x 100 mm bis 20 x 100 mm
- 8 x 1.50 mm bis 16 x 1.50 mm

General ordering data

Version	SAI Passive, Sensor-actuator passive distributor, Hood version with M25 outlet
Order No.	1752083000
Type	SAI 4/6/8 MH-MHD BLZF
GTIN (EAN)	4032248269198
Qty.	640 pc(s).

SAI 4/6/8 MH-MHD BLZF

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	56.9 mm	Depth (inches)	2.24 inch
Height	44.5 mm	Height (inches)	1.752 inch
Net weight	100 g	Width	59.2 mm
Width (inches)	2.331 inch		

Temperatures

Operating temperature	-
-----------------------	---

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Connection data

Conductor O.D., min.	14 mm	Conductor O.D., max.	18 mm
Cable glands	M 25	Distributor outlet	Hood version with M25 outlet

Electrical data

Rated voltage, min.	10 V	Rated voltage, max.	30 V
Max. current-carrying capacity per slot	4 A		

General technical data

Protection degree	IP68	Pollution severity	3
-------------------	------	--------------------	---

Material data

Housing main material	Zinc diecast (hood)	Contact material	CuZn
Contact surface	Gold-plated		

Technical data cable

Conductor O.D., max.	18 mm	Conductor O.D., min.	14 mm
Suitable for cable carriers	No		

Classifications

ETIM 6.0	EC002585	ETIM 7.0	EC003558
ECLASS 9.0	27-44-01-08	ECLASS 9.1	27-44-01-08
ECLASS 10.0	27-44-01-11	ECLASS 11.0	27-44-01-11

Approvals

Approvals



ROHS	Conform
------	---------