

**BLZF BW-S****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Example of use**

Similar to illustration

**More intelligent. More efficient. Quicker.**

Auxiliary tools simplify the process of connecting and configuring the connection components:

- Assembly blocks for socket connectors with IDC contacts (type BL-IDC) can be used in machines such as toggle lever presses. All conductors are connected at the same time.
- Unlocking and dismantling tools release the crimp contacts in crimped plug-in connectors (type BLC & BLAC)
- Operating levers open individual clamping points on plug-in tension clamp connectors

For better, more rapid working progress

The result: efficient, professional working progress.

**General ordering data**

|                 |                                                                |
|-----------------|----------------------------------------------------------------|
| Version         | OMNIMATE Power - Powerbus series, PCB plug-in connector        |
| Order No.       | <a href="#">1764080000</a>                                     |
| Type            | BLZF BW-S                                                      |
| GTIN (EAN)      | 4032248060467                                                  |
| Qty.            | 100 pc(s).                                                     |
| Product data    |                                                                |
| Packaging       | Box                                                            |
| Delivery status | <b>This article will no longer be available in the future.</b> |
| Available until | 2023-12-31                                                     |

Creation date March 25, 2021 4:13:22 AM CET

**BLZF BW-S****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|            |       |
|------------|-------|
| Net weight | 0.3 g |
|------------|-------|

**Material data**

|                                       |        |                                       |          |
|---------------------------------------|--------|---------------------------------------|----------|
| Colour                                | white  | Colour chart (similar)                | RAL 9010 |
| Storage temperature, min.             | -40 °C | Storage temperature, max.             | 70 °C    |
| Operating temperature, min.           | -50 °C | Operating temperature, max.           | 100 °C   |
| Temperature range, installation, min. | -25 °C | Temperature range, installation, max. | 100 °C   |

**Rated data acc. to IEC**

|                         |                        |
|-------------------------|------------------------|
| tested acc. to standard | IEC 60664-1, IEC 61984 |
|-------------------------|------------------------|

**Packing**

|           |       |            |       |
|-----------|-------|------------|-------|
| Packaging | Box   | VPE length | 10 mm |
| VPE width | 60 mm | VPE height | 90 mm |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000149    | ETIM 7.0    | EC000149    |
| ECLASS 9.0  | 21-04-50-03 | ECLASS 9.1  | 21-01-90-90 |
| ECLASS 10.0 | 21-04-50-03 | ECLASS 11.0 | 21-04-50-03 |

**Important note**

|                |                                                                                                                                                                                                                                                                                                                            |
|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| IPC conformity | Conformity: The products are developed, manufactured and delivered according international recognized standards and norms and comply with the assured properties in the data sheet resp. fulfill decorative properties in accordance with IPC-A-610 "Class 2". Further claims on the products can be evaluated on request. |
| Notes          | <ul style="list-style-type: none"> <li>Long term storage of the product with average temperature of 50 °C and average humidity 70%, 36 months</li> </ul>                                                                                                                                                                   |

**Approvals**

Approvals



|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                                             |                                                 |
|---------------------------------------------|-------------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">Declaration of the Manufacturer</a> |
|---------------------------------------------|-------------------------------------------------|