

LM WO 37/25 GE**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Similar to illustration

Self-adhesive polyester labels which are suitable for A4 office laser printer.

General ordering data

Version	LaserMark, Conductor and cable markers, 3.4 - 4.8 mm, {Reference (AttributeDefinition) not found: pAttr74196859207437}, yellow
Order No.	1768430000
Type	LM WO 37/25 GE
GTIN (EAN)	4032248110070
Qty.	10 pc(s).

LM WO 37/25 GE

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	0.025 mm	Depth (inches)	0.001 inch
Height	37 mm	Height (inches)	1.457 inch
Net weight	10.2 g	Width	25 mm
Width (inches)	0.984 inch		

Temperatures

Operating temperature range	-40...150 °C
-----------------------------	--------------

General data

Adhesive	Acrylate	Colour	yellow
Halogen	No	Material	Polyester film
Material colour according to resistance code		Number of markers per combination	1 Label sheet = 55 Conductor and cable markers
	4		
Number per sheet	55	Operating temperature range	-40...150 °C
Operating temperature range, max.	150 °C	Operating temperature range, min.	-40 °C
Size of labelling field	37 x 8 mm	Type of printing	neutral
UL 94 flammability rating	V-0	Version	Self-adhesive
Width	25 mm		

Conductor and cable markers

Conductor O.D.	3.4 - 4.8 mm	Conductor O.D., max.	4.8 mm
Conductor O.D., min.	3.4 mm	Conductor cross-section, max.	6 mm ²
Conductor cross-section, min.	2.5 mm ²	Cross-section for connected wire	2.5 - 6 mm ²
Halogen	No	Text field height	8 mm
Text field width	35.5 mm		

Classifications

ETIM 6.0	EC001530	ETIM 7.0	EC001530
ECLASS 9.0	27-40-04-01	ECLASS 9.1	27-40-04-01
ECLASS 10.0	27-40-04-01	ECLASS 11.0	27-28-11-02

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	STEP
Engineering Data	EPLAN, WSCAD, Zuken E3.S

LM WO 37/25 GE

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Drawings

