

**HDC 10B SLU 2M20G****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

**General ordering data**

|            |                                                                                                                                                             |
|------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Version    | HDC enclosures, Size: 4, Protection degree: IP65 (in plugged condition), Base housing, End-locking clamp, lower side, Standard, Size of cable entries: M 20 |
| Order No.  | <a href="#">1787660000</a>                                                                                                                                  |
| Type       | HDC 10B SLU 2M20G                                                                                                                                           |
| GTIN (EAN) | 4032248205004                                                                                                                                               |
| Qty.       | 1 pc(s).                                                                                                                                                    |

**HDC 10B SLU 2M20G****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|                             |            |                            |            |
|-----------------------------|------------|----------------------------|------------|
| Height                      | 57 mm      | Height (inches)            | 2.244 inch |
| Mounting dimension - height | 40 mm      | Mounting dimension - width | 82 mm      |
| Net weight                  | 270 g      | Width                      | 77.7 mm    |
| Width (inches)              | 3.059 inch |                            |            |

**Temperatures**

|                   |                   |
|-------------------|-------------------|
| Limit temperature | -40 °C ... 125 °C |
|-------------------|-------------------|

**Environmental Product Compliance**

|                     |                                                                |                         |
|---------------------|----------------------------------------------------------------|-------------------------|
| REACH SVHC          | Lead 7439-92-1, Potassium perfluorobutane sulfonate 29420-49-3 |                         |
| Chemical resistance | Substance                                                      | Acetone                 |
|                     | Chemical resistance                                            | Conditionally resistant |
|                     | Substance                                                      | Drilling oil            |
|                     | Chemical resistance                                            | Resistant               |
|                     | Substance                                                      | Diesel                  |
|                     | Chemical resistance                                            | Resistant               |
|                     | Substance                                                      | Ethyl alcohol           |
|                     | Chemical resistance                                            | Resistant               |
|                     | Substance                                                      | Transmission oil        |
|                     | Chemical resistance                                            | Resistant               |
|                     | Substance                                                      | Hydraulic oil           |
|                     | Chemical resistance                                            | Resistant               |
|                     | Substance                                                      | Coolant                 |
|                     | Chemical resistance                                            | Resistant               |
|                     | Substance                                                      | Petroleum benzene       |
|                     | Chemical resistance                                            | Resistant               |
|                     | Substance                                                      | Sweat                   |
|                     | Chemical resistance                                            | Resistant               |
|                     | Substance                                                      | Premium gasoline        |
|                     | Chemical resistance                                            | Conditionally resistant |
|                     | Substance                                                      | Water                   |
|                     | Chemical resistance                                            | Resistant               |
|                     | Substance                                                      | UV                      |
|                     | Chemical resistance                                            | Unstable                |
|                     | Substance                                                      | Ozone                   |
|                     | Chemical resistance                                            | Unstable                |

**Dimensions**

|                      |              |                      |         |
|----------------------|--------------|----------------------|---------|
| Cable entry          | w. threading | Height of base B1    | 5 mm    |
| Height of housing B  | 57 mm        | Hole pitch length A2 | 82 mm   |
| Total length housing | 73 mm        | Width base C1        | 53.5 mm |
| Width housing C      | 43 mm        |                      |         |

**General data**

|                             |                             |                       |                             |
|-----------------------------|-----------------------------|-----------------------|-----------------------------|
| EMC housings                | No                          | Housing main material | diecast aluminium           |
| Material of locking element | Stainless steel, rust-proof | Protection degree     | IP65 (in plugged condition) |
| Surface finish              |                             | Tightening torque     | 1.2 Nm                      |

## HDC 10B SLU 2M20G

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Version

|                              |                               |                                |                   |
|------------------------------|-------------------------------|--------------------------------|-------------------|
| Cable entry                  | w. threading                  | Clamp version                  | End-locking clamp |
| Design                       | Standard                      | Design of housing              | Base housing      |
| Design of locking system     | End-locking clamp, lower side | Internal thread                | M 20              |
| Number of cable entry on top | 0                             | Number of cable entry sideways | 2                 |
| Sealing                      | NBR                           | Size                           | 4                 |
| Size of cable entries        | M 20                          | Suitable for ModuPlug®         | No                |
| Tightening torque            | 1.2 Nm                        | Top part/bottom part/lid       | lower part        |
| Type                         | Base housing                  |                                |                   |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000437    | ETIM 7.0    | EC000437    |
| ECLASS 9.0  | 27-44-02-02 | ECLASS 9.1  | 27-44-02-02 |
| ECLASS 10.0 | 27-44-02-02 | ECLASS 11.0 | 27-44-02-02 |

## Approvals

Approvals



ROHS

Conform

## Downloads

|                                             |                                                               |
|---------------------------------------------|---------------------------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">Manufacturer's declaration</a>                    |
| Engineering Data                            | <a href="#">STEP</a>                                          |
| Engineering Data                            | <a href="#">EPLAN, WSCAD</a>                                  |
| Technical Documentation                     | <a href="#">1787660000_HDC_10B_SLU_2M20G_STP_Blatt__1.pdf</a> |