

**CC-H 15/27****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

Similar to illustration

**General ordering data**

|            |                                                                                                |
|------------|------------------------------------------------------------------------------------------------|
| Version    | ClipCard, Accessories, [Reference (AttributeDefinition) not found: pAttr74196859207437], black |
| Order No.  | <a href="#">1790410000</a>                                                                     |
| Type       | CC-H 15/27                                                                                     |
| GTIN (EAN) | 4032248215201                                                                                  |
| Qty.       | 45 pc(s).                                                                                      |

## CC-H 15/27

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|                |            |                 |            |
|----------------|------------|-----------------|------------|
| Depth          | 5.5 mm     | Depth (inches)  | 0.217 inch |
| Height         | 15 mm      | Height (inches) | 0.591 inch |
| Net weight     | 0.996 g    | Width           | 27 mm      |
| Width (inches) | 1.063 inch |                 |            |

## Temperatures

|                             |              |
|-----------------------------|--------------|
| Operating temperature range | -40...100 °C |
|-----------------------------|--------------|

## General data

|                                   |              |                                   |                           |
|-----------------------------------|--------------|-----------------------------------|---------------------------|
| Colour                            | black        | Halogen                           | No                        |
| Material                          | Polyamide 66 | Number of markers per combination | 1 MultiCard = Accessories |
| Operating temperature range       | -40...100 °C | Operating temperature range, max. | 100 °C                    |
| Operating temperature range, min. | -40 °C       | Recommended industries            | Machinery                 |
| UL 94 flammability rating         | V-2          | Width                             | 27 mm                     |

## Device markers

|         |    |
|---------|----|
| Halogen | No |
|---------|----|

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001288    | ETIM 7.0    | EC001288    |
| ECLASS 9.0  | 27-40-06-29 | ECLASS 9.1  | 27-40-06-29 |
| ECLASS 10.0 | 27-40-06-29 | ECLASS 11.0 | 27-28-11-04 |

## Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## Downloads

|                  |                              |
|------------------|------------------------------|
| Engineering Data | <a href="#">STEP</a>         |
| Engineering Data | <a href="#">EPLAN, WSCAD</a> |