KLBUE 3-8 SC

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Product image

Shielding and earthing
Our protective earth conductor and shielding terminals featuring different connection technologies allow you to effectively protect both people and equipment from interference, such as electrical or magnetic fields. A comprehensive range of accessories rounds off our range.

General ordering data

Version	Clamping yoke, Clamping yoke, Steel
Order No.	1791220000
Type	KLBUE 3-8 SC
GTIN (EAN)	4032248222179
Qty.	100 pc(s).

KLBUE 3-8 SC

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	26 mm	Depth (inches)	1.024 inch
Height	18.5 mm	Height (inches)	0.728 inch
Mounting dimension - width	13.5 mm	Net weight	11.86 g
Width	14.5 mm	Width (inches)	0.571 inch

Temperatures

Storage temperature	-25 °C...55 °C

Material data

Material	Steel	Colour	silver

System specifications

Version	For a shield connection

Additional technical data

Explosion-tested version	No	Installation advice	Direct mounting
Type of mounting	Screw		

Conductors for clamping (rated connection)

Cable diameter, max.	8 mm	Cable diameter, min.	3 mm

General

Installation advice	Direct mounting

Classifications

ETIM 6.0	EC002020	ETIM 7.0	EC002020
ECLASS 9.0	27-14-11-50	ECLASS 9.1	27-14-11-50
ECLASS 10.0	27-14-11-50	ECLASS 11.0	27-14-11-50

Approvals

Approvals	
ROHS	Conform

Downloads

Approval/Certificate/Document of Conformity	EAC certificate
Engineering Data	STEP
Engineering Data	EPLAN
User Documentation	Beipackzettel_KLBUE.pdf StorageConditionsTerminalBlocks