

TM 207/15 V0**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



Similar to illustration

Our extensive range of TM sleeves is suitable for all-purpose use. They cover a wide range of applications: from thin conductors to cables with large external diameters. This range offers printed inlay tags with maximum protection against outside influences. TM sleeves permit flexible installation.

- Optimum protection for printed inlay tags
- Wide range of applications for conductors and cables
- One tag type for all cross-sections
- TMX 30 for mounting with cable ties (width 4.6 mm)

General ordering data

Version	TM, Socket x 30 mm, PVC, Colour: Transparent, Conductor O.D.: 22 - 30 mm
Order No.	1806270000
Type	TM 207/15 V0
GTIN (EAN)	4032248275786
Qty.	50 pc(s).
Delivery status	This article will no longer be available in the future.
Available until	2018-11-30
Alternative product	1866680000

Creation date March 25, 2021 11:56:47 AM CET

TM 207/15 V0

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	30 mm	Depth (inches)	1.181 inch
Height	15 mm	Height (inches)	0.591 inch
Net weight	2.58 g	Width	30 mm
Width (inches)	1.181 inch		

Temperatures

Operating temperature range	-40...80 °C
-----------------------------	-------------

General data

Colour	Transparent	Material	PVC
Operating temperature range	-40...80 °C	Operating temperature range, max.	80 °C
Operating temperature range, min.	-40 °C	Recommended industries	Transportation, Machinery
Type of printing	neutral	UL 94 flammability rating	V-0
Width	30 mm		

Conductor and cable markers

Conductor O.D.	22 - 30 mm	Conductor O.D., max.	30 mm
Conductor O.D., min.	22 mm	Conductor cross-section, max.	240 mm ²
Conductor cross-section, min.	120 mm ²	Cross-section for connected wire	120 - 240 mm ²

Classifications

ETIM 6.0	EC001530	ETIM 7.0	EC001530
ECLASS 9.0	27-40-04-01	ECLASS 9.1	27-40-04-01
ECLASS 10.0	27-40-04-01	ECLASS 11.0	27-28-11-02

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	STEP
Engineering Data	EPLAN, WSCAD, Zuken E3.S