

SAISW-5/9

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com







Individual cable lengths are often required nowadays. In order to meet these demands, Weidmüller offers a wide range of plug-in connectors for custom assembly. Male plugs and female socket for customisable assembly for M8, M12, M16 and 7/8" connections which are highly robust and ideally suited to machine engineering, for instance. The M12 plug-in connectors offer a choice of 5 different connection systems.

The screw connection can be used in a wide range of applications. With this technology the conductor, optionally with wire-end ferrules, can be plugged into connection elements and secured with a screw. It is the classic, cheapest form of connection technology that also supports multi-conductor connections.

General ordering data

| Version | Plugs prefabricated to customer spec., M12, pin, 90° |
|------------|--|
| Order No. | <u>1807370000</u> |
| Туре | SAISW- 5/9 |
| GTIN (EAN) | 4032248278596 |
| Qty. | 1 pc(s). |



SAISW-5/9

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Dimensions and weights

Net weight 26 g

Environmental Product Compliance

REACH SVHC Lead 7439-92-1,

Imidazolidine-2-thione

96-45-7

Technical data customisable plug-in connectors

| Cable diameter | 46 mm (PG7)/ 68 mm | Cable diameter, max. | |
|--------------------------------|---------------------------|--------------------------------|----------------------|
| | (PG9) | | 8 mm |
| Cable diameter, min. | 6 mm | Coding | Α |
| Conductor cross-section, max. | 0.75 mm ² | Conductor cross-section, min. | 0.14 mm ² |
| Connection cross-section, max. | 0.75 mm ² | Connection cross-section, min. | 0.14 mm ² |
| Contact surface | CuSnZn | Contact surface | CuSnZn |
| Housing main material | PA | Insulation strength | 10 ⁸ Ω |
| Number of poles | 5 | Plugging cycles | ≥ 50 |
| Pollution severity | 3 | Protection degree | IP67 |
| Rated current | 4 A | Rated voltage | 60 V |
| Rated voltage (text) | 250 V (4-pole) / 60 V (5- | Shield connection | |
| | pole) / 30 V (8-pole) | | No |
| Temperature range of housing | -40 +85 ° C | Threaded ring material | Diecast zinc |
| Type of connection | Screw connection | | |

Standards

Connector standard IEC 61076-2-101

Classifications

| ETIM 6.0 | EC002635 | ETIM 7.0 | EC002635 |
|-------------|-------------|-------------|-------------|
| ECLASS 9.0 | 27-44-01-02 | ECLASS 9.1 | 27-44-01-03 |
| ECLASS 10.0 | 27-44-01-02 | ECLASS 11.0 | 27-44-01-02 |

Approvals

Approvals



| ROHS | Conform | |
|-----------------------|---------|--|
| UL File Number Search | E307231 | |

Downloads

| Engineering Data | <u>STEP</u> | |
|--------------------|---------------|--|
| Engineering Data | WSCAD | |
| User Documentation | <u>Manual</u> | |



SAISW-5/9

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Drawings

Pole scheme

