

**SAISW-4-IDC M12****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

Individual cable lengths are often required nowadays. In order to meet these demands, Weidmüller offers a wide range of plug-in connectors for custom assembly. Male plugs and female socket for customisable assembly for M8, M12, M16 and 7/8" connections which are highly robust and ideally suited to machine engineering, for instance. The M12 plug-in connectors offer a choice of 5 different connection systems.

The IDC is simple and quick to assemble since this technology allows the conductor to be inserted directly into the terminal point, without crimping or having to strip the insulation. It also has excellent functional security.

**General ordering data**

|            |                                                          |
|------------|----------------------------------------------------------|
| Version    | Plugs prefabricated to customer spec., M12, pin, 90&deg; |
| Order No.  | <a href="#">1812870000</a>                               |
| Type       | SAISW-4-IDC M12                                          |
| GTIN (EAN) | 4032248296422                                            |
| Qty.       | 1 pc(s).                                                 |

Creation date March 25, 2021 12:59:00 PM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

## SAISW-4-IDC M12

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |      |
|------------|------|
| Net weight | 26 g |
|------------|------|

## Environmental Product Compliance

|            |                |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

## Technical data customisable plug-in connectors

|                                |                     |                                |                                    |
|--------------------------------|---------------------|--------------------------------|------------------------------------|
| Cable diameter                 | 4...5.1 mm          | Cable diameter, max.           | 5.1 mm                             |
| Cable diameter, min.           | 4 mm                | Coding                         | A                                  |
| Conductor cross-section, max.  | 0.5 mm <sup>2</sup> | Conductor cross-section, min.  | 0.25 mm <sup>2</sup>               |
| Connection cross-section, max. | 0.5 mm <sup>2</sup> | Connection cross-section, min. | 0.25 mm <sup>2</sup>               |
| Contact surface                | tinned              | Housing main material          | CuZn                               |
| Insulation strength            | 10 <sup>8</sup> Ω   | Number of poles                | 4                                  |
| Plugging cycles                | ≥ 50                | Pollution severity             | 3                                  |
| Protection degree              | IP67                | Rated current                  | 4 A                                |
| Rated voltage                  | 32 V                | Rated voltage (text)           | 32 V                               |
| Shield connection              | No                  | Temperature range of housing   | -25...+85 °C                       |
| Threaded ring material         | Diecast zinc        | Type of connection             | Insulation displacement connection |

## Standards

|                    |                 |
|--------------------|-----------------|
| Connector standard | IEC 61076-2-101 |
|--------------------|-----------------|

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC002635    | ETIM 7.0    | EC002635    |
| ECLASS 9.0  | 27-44-01-02 | ECLASS 9.1  | 27-44-01-03 |
| ECLASS 10.0 | 27-44-01-02 | ECLASS 11.0 | 27-44-01-02 |

## Approvals

Approvals



|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## Downloads

|                    |                        |
|--------------------|------------------------|
| Engineering Data   | <a href="#">WSCAD</a>  |
| User Documentation | <a href="#">Manual</a> |