



Main

Relay application	Remote control
Range of product	C120 C60
Device short name	ATm7
Signal contacts composition	1 NC 1 NO 7 NO
Number of feeders controlled	7

Complementary

Reset	Non differential general electric fault Differential source of the fault
Control type	Automatic
Local signalling	LCD display unit
Type of setting	Fault count On/Off State of the feeders Time delay configuration Type fault
Signalling circuit voltage	AC: 230 V 50/60 Hz
Signalling output current	8 A
[Us] rated supply voltage	250 V AC 50/60 Hz
Supply maximum power	7 VA
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
Height	81 mm
Width	71.2 mm
Depth	60 mm
Product weight	0.325 kg
Auxiliary connection terminal	Tunnel type terminal 2 pin(s) rigid 1.5 mm ² Tunnel type terminal 1 pin(s) flexible 2.5 mm ²

Environment

Standards	EN 60601-1 EN 60730-1 EN 60947-1
IP degree of protection	IP4 conforming to EN 60947-1 IP4 conforming to EN 60730-1 IP4 conforming to EN 60601-1
Electrical shock protection class	Class II
Tropicalisation	2 conforming to EN 60947-1 2 conforming to EN 60730-1 2 conforming to EN 60601-1
Relative humidity	95 % (55 °C)
Operating altitude	2000 m
Ambient air temperature for operation	-5...55 °C
Ambient air temperature for storage	-40...70 °C

Contractual warranty

Period	18 months
--------	-----------