

**WQV 50N/3****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Product image****Power feed-in**

Our wide range of W-Series terminal blocks with our WPD main line branch terminals, which are optimised to guarantee both convenience and space gains, ensures a secure and convenient connection at the power feed-in.

**General ordering data**

|            |                                                                     |
|------------|---------------------------------------------------------------------|
| Version    | W-Series, Cross-connector, For the terminals,<br>Number of poles: 3 |
| Order No.  | <a href="#">1834070000</a>                                          |
| Type       | WQV 50N/3                                                           |
| GTIN (EAN) | 4032248379866                                                       |
| Qty.       | 5 pc(s).                                                            |

## WQV 50N/3

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|                |            |                 |            |
|----------------|------------|-----------------|------------|
| Depth          | 17.5 mm    | Depth (inches)  | 0.689 inch |
| Height         | 47 mm      | Height (inches) | 1.85 inch  |
| Net weight     | 35.21 g    | Width           | 9.5 mm     |
| Width (inches) | 0.374 inch |                 |            |

## Temperatures

|                     |                |
|---------------------|----------------|
| Storage temperature | -25 °C...55 °C |
|---------------------|----------------|

## Material data

|          |               |        |             |
|----------|---------------|--------|-------------|
| Material | tinned copper | Colour | Silver grey |
|----------|---------------|--------|-------------|

## System specifications

|         |                   |
|---------|-------------------|
| Version | For the terminals |
|---------|-------------------|

## Additional technical data

|                     |                 |                |                 |
|---------------------|-----------------|----------------|-----------------|
| Installation advice | Direct mounting | Type of fixing | when screwed in |
|---------------------|-----------------|----------------|-----------------|

## Cross-connector

|                                     |                 |                           |       |
|-------------------------------------|-----------------|---------------------------|-------|
| Number of cross-connected terminals | 3               | Rated current, multi-pole | 150 A |
| Type                                | Cross-connector |                           |       |

## Dimensions

|                 |         |
|-----------------|---------|
| Pitch in mm (P) | 18.5 mm |
|-----------------|---------|

## General

|                     |                 |                 |   |
|---------------------|-----------------|-----------------|---|
| Installation advice | Direct mounting | Number of poles | 3 |
|---------------------|-----------------|-----------------|---|

## Rating data

|               |       |
|---------------|-------|
| Rated current | 150 A |
|---------------|-------|

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000489    | ETIM 7.0    | EC000489    |
| ECLASS 9.0  | 27-14-11-40 | ECLASS 9.1  | 27-14-11-40 |
| ECLASS 10.0 | 27-14-11-40 | ECLASS 11.0 | 27-14-11-40 |

## Approvals

Approvals



ROHS

Conform

## WQV 50N/3

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Downloads

|                                             |                                                             |
|---------------------------------------------|-------------------------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">EAC certificate</a>                             |
| Engineering Data                            | <a href="#">STEP</a>                                        |
| Engineering Data                            | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>                    |
| User Documentation                          | <a href="#">StorageConditionsTerminalBlocks Instruction</a> |