

TS 35X15/2.3 2M/AL/BK**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Product image**

Similar to illustration

Building installation wiring

For building installations, we offer a complete system that revolves around the 10×3 copper rail and comprises perfectly coordinated components: from installation terminal blocks, neutral conductor terminal blocks and distribution terminal blocks to comprehensive accessories such as busbars and busbar holders.

General ordering data

Version	Rail, TS 35, TS 35 x 15, without slot, Aluminium, untreated
Order No.	1848290000
Type	TS 35X15/2.3 2M/AL/BK
GTIN (EAN)	4032248385614
Qty.	2 m

TS 35X15/2.3 2M/AL/BK

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	15 mm	Depth (inches)	0.591 inch
Height	35 mm	Height (inches)	1.378 inch
Net weight	330 g	Width	2,000 mm
Width (inches)	78.74 inch		

Mounting rail

Installation advice	Direct mounting	
Length of the terminal rail	min.	0 mm
	max.	2,000 mm
	nominal	2,000 mm
Material	Aluminium	
Permitted thermal current for PEN function, max.	232 A	
Pre-punched mounting rail	No	
Short circuit strength corresponds to E-Cu wire	95 mm²	
Short-time withstand current according to IEC 60947-7-2	11.4 kA/1s	
Slit gap		
Slit length		
Slit width		
Standards	DIN EN 60715	
Surface finish	untreated	
Thickness	2.3 mm	

Classifications

ETIM 6.0	EC001285	ETIM 7.0	EC001285
ECLASS 9.0	27-40-06-02	ECLASS 9.1	27-40-06-02
ECLASS 10.0	27-40-06-02	ECLASS 11.0	27-40-06-02

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	STEP
Engineering Data	EPLAN, WSCAD, Zuken E3.S
User Documentation	StorageConditionsTerminalBlocks