

SAI-8-F 5P CNOMO 10M

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



Whereas the standard M12 system requires the sleeves to be laboriously screwed on and that operation is hindered by the vibration guard, M12 Push-Pull works with one click, just like those well-known garden hose systems. The audible locking function guarantees a safe and reliable connection as well as a good seal. The new SAI M12 Push-Pull distributors can be used with M12 plug-in connectors but also with the new M12 Push-Pull plug-in connectors.

General ordering data

Version	Sensor-actuator passive distributor, Push-Pull, M12, Fixed cable version, 10 m, No
Order No.	1861590000
Type	SAI-8-F 5P CNOMO 10M
GTIN (EAN)	4032248421879
Qty.	1 pc(s).
Delivery status	Discontinued
Available until	2019-03-01

Creation date March 25, 2021 9:05:09 PM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

SAI-8-F 5P CNOMO 10M

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Height	26 mm	Height (inches)	1.024 inch
Net weight	2,020 g	Width	54 mm
Width (inches)	2.126 inch		

Temperatures

Operating temperature	-25 - 80°C
-----------------------	------------

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Connection data

Sheathing stripping length	100 mm	Distributor outlet	Fixed cable version
----------------------------	--------	--------------------	---------------------

Electrical data

Rated voltage, min.	10 V	Rated voltage, max.	50 V
Test voltage	1 kV	Max. current-carrying capacity per slot	4 A
Total current	8 A	Current per signal	2 A
Electrical isolation available	No	Insulation strength	10 ⁹ Ω

General technical data

Plug-in station coding	A	Protection degree	IP67
Number of poles	5	Number of contact sockets	8
Connection thread	M12	Pollution severity	3
Fire behaviour	V-0	LED	No
LED initiator	No		

Material data

Housing main material	PA 6 GF	Material of distributor	Plastic
Housing colour	grey, RAL 7032	Screw socket	Nickel-plated CuZn
Contact material	CuZn	Contact surface	Gold-plated
Contact carrier material	PBT (UL 94 V0)		

Technical data cable

Bending radius, min., moving	10 x cable diameter	Bending radius, min., stationary	5 x cable diameter
Colour coding	grey / pink, white, red / blue, green, white / green, yellow, brown / green, grey, white / yellow, pink, Yellow / brown, red, white / grey, black, grey / brown, violet, blue, brown, Green/yellow	Number of poles	5
O.D.	10.5 mm	Sheathing colour	Pebble grey
Wire cross section	16 x 0.34 mm ² + 3 x 1.0 mm ²	Cable length	10 m
Suitable for cable carriers	Yes		

Creation date March 25, 2021 9:05:09 PM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

2

SAI-8-F 5P CNOMO 10M

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

Classifications

ETIM 6.0	EC002585	ETIM 7.0	EC002585
ECLASS 9.0	27-44-01-08	ECLASS 9.1	27-44-01-08
ECLASS 10.0	27-44-01-08	ECLASS 11.0	27-44-01-08

Approvals

Approvals



ROHS Conform

Downloads

Engineering Data [WSCAD](#)


SAI-8-F 5P CNOMO 10M

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Drawings

Dimensioned drawing



Wiring diagram

