

**ZVLA SC ZPS2.5****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Product image****Building installation wiring**

For building installations, we offer a complete system that revolves around the 10×3 copper rail and comprises perfectly coordinated components: from installation terminal blocks, neutral conductor terminal blocks and distribution terminal blocks to comprehensive accessories such as busbars and busbar holders.

**General ordering data**

|            |                                                    |
|------------|----------------------------------------------------|
| Version    | Z-series, Plug-in modular terminals, yellow, 15 mm |
| Order No.  | <a href="#">1866240000</a>                         |
| Type       | ZVLA SC ZPS2.5                                     |
| GTIN (EAN) | 4032248513376                                      |
| Qty.       | 20 pc(s).                                          |

## ZVLA SC ZPS2.5

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|                |            |                 |            |
|----------------|------------|-----------------|------------|
| Depth          | 26 mm      | Depth (inches)  | 1.024 inch |
| Height         | 73.8 mm    | Height (inches) | 2.906 inch |
| Net weight     | 5 g        | Width           | 15 mm      |
| Width (inches) | 0.591 inch |                 |            |

## Temperatures

|                                  |                |                                  |     |
|----------------------------------|----------------|----------------------------------|-----|
| Storage temperature              | -25 °C...55 °C | Continuous operating temp., min. | -50 |
| Continuous operating temp., max. | 100            |                                  |     |

## Material data

|                           |             |        |        |
|---------------------------|-------------|--------|--------|
| Material                  | PA 66 GF 30 | Colour | yellow |
| UL 94 flammability rating | HB          |        |        |

## System specifications

|         |                   |
|---------|-------------------|
| Version | Intermediate part |
|---------|-------------------|

## Additional technical data

|                     |                 |
|---------------------|-----------------|
| Installation advice | Direct mounting |
|---------------------|-----------------|

## Conductors for clamping (rated connection)

|                    |                    |
|--------------------|--------------------|
| Type of connection | Plug-in connection |
|--------------------|--------------------|

## General

|                     |                 |
|---------------------|-----------------|
| Installation advice | Direct mounting |
|---------------------|-----------------|

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC002848    | ETIM 7.0    | EC002848    |
| ECLASS 9.0  | 27-14-11-92 | ECLASS 9.1  | 27-14-11-92 |
| ECLASS 10.0 | 27-14-11-92 | ECLASS 11.0 | 27-14-11-92 |

## Approvals

Approvals



|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## Downloads

|                                             |                                                                                          |
|---------------------------------------------|------------------------------------------------------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">DNVGL certificate</a>                                                        |
| Engineering Data                            | <a href="#">STEP</a>                                                                     |
| Engineering Data                            | <a href="#">EPLAN, WSCAD</a>                                                             |
| User Documentation                          | <a href="#">Beipackzettel_ZPS.pdf</a><br><a href="#">StorageConditionsTerminalBlocks</a> |