

**SAI-10-S12 3P M8 L****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

The new slim M8 line from Weidmüller. This range of products is characterised by the marking options at all connection positions. Even the 4-way distributor with 8-pole M12 has adequately large markers at all M8 connection positions. Furthermore, this distributor is shorter than many conventional M8 designs.

- Very narrow, short and flat M8 distributor.
- The range is supplied with 4 to 12 M8 connection positions, 3 or 4 poles.
- Hybrid variants of the M8 are also possible on request.
- The M8 line is equipped with transverse holes.

**General ordering data**

|            |                                                                                              |
|------------|----------------------------------------------------------------------------------------------|
| Version    | SAI Passive, Sensor-actuator passive distributor, M8, with M12 outlet, 12-pole, A-coded, Yes |
| Order No.  | <a href="#">1877950000</a>                                                                   |
| Type       | SAI-10-S12 3P M8 L                                                                           |
| GTIN (EAN) | 4032248528707                                                                                |
| Qty.       | 1 pc(s).                                                                                     |

## SAI-10-S12 3P M8 L

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |       |
|------------|-------|
| Net weight | 128 g |
|------------|-------|

## Temperatures

|                       |            |
|-----------------------|------------|
| Operating temperature | -25 - 80°C |
|-----------------------|------------|

## Environmental Product Compliance

|            |                |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

## Connection data

|                            |        |                    |                                   |
|----------------------------|--------|--------------------|-----------------------------------|
| Sheathing stripping length | 100 mm | Distributor outlet | with M12 outlet, 12-pole, A-coded |
|----------------------------|--------|--------------------|-----------------------------------|

## Electrical data

|                     |                   |                                         |      |
|---------------------|-------------------|-----------------------------------------|------|
| Rated voltage, min. | 10 V              | Rated voltage, max.                     | 30 V |
| Test voltage        | 1 kV              | Max. current-carrying capacity per slot | 2 A  |
| Total current       | 6 A               | Current per signal                      | 1 A  |
| Insulation strength | 10 <sup>9</sup> Ω |                                         |      |

## General technical data

|                                     |       |                             |        |
|-------------------------------------|-------|-----------------------------|--------|
| Protection degree                   | IP68  | Number of poles             | 3      |
| Number of contact sockets           | 10    | Connection thread           | M8     |
| Pollution severity                  | 3     | Fire behaviour              | V-0    |
| LED                                 | Yes   | LED initiator               | Yes    |
| LED colour for indicating operation | green | LED colour for I/O function | yellow |

## Material data

|                          |                |                         |                    |
|--------------------------|----------------|-------------------------|--------------------|
| Housing main material    | Pocan          | Material of distributor | Plastic            |
| Housing colour           | grey, RAL 7032 | Screw socket            | Nickel-plated CuZn |
| Contact material         | CuZn           | Contact surface         | Gold-plated        |
| Contact carrier material | PBT (UL 94 V0) |                         |                    |

## Technical data cable

|                 |   |                             |    |
|-----------------|---|-----------------------------|----|
| Number of poles | 3 | Suitable for cable carriers | No |
|-----------------|---|-----------------------------|----|

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC002585    | ETIM 7.0    | EC003558    |
| ECLASS 9.0  | 27-44-01-08 | ECLASS 9.1  | 27-44-01-08 |
| ECLASS 10.0 | 27-44-01-11 | ECLASS 11.0 | 27-44-01-11 |

## SAI-10-S12 3P M8 L

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Approvals

Approvals



|                       |         |
|-----------------------|---------|
| ROHS                  | Conform |
| UL File Number Search | E92202  |

### Downloads

|                  |                       |
|------------------|-----------------------|
| Engineering Data | <a href="#">STEP</a>  |
| Engineering Data | <a href="#">WSCAD</a> |


## SAI-10-S12 3P M8 L

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

# Drawings

## Dimensioned drawing



## Wiring diagram

