

#### **SLA BB11R OR SO**

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

### **Product image**







Similar to illustration

#### Minor component, major effect:

Clip-on attachment elements increase the mechanical resilience of the whole plug connection by

- securing the male connectors to the circuit board
- providing a vibration-proof connection between the sockets and the male connectors

Clip-on or pre-assembled - always the right solution:

- Hard-wearing, precise fitting dovetail joint
- Hard-wearing metal threaded inserts
- · Suitable for all outlet directions

Maximum stability, minimum effort:

- Extremely resilient for frequent fastening operations
- Complete set for easy selection

The result: soldering points, contacts and overall module are more resilient against mechanical stress such as vibrations and tensile loads.

#### **General ordering data**

PCB plug-in connector, Accessories, Mounting block, orange, Number of poles: 1
<u>1879880000</u>
SLA BB11R OR SO
4032248476961
100 pc(s).
Вох



#### **SLA BB11R OR SO**

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Technical data**

ь.	-		
Dim	ensions	and	weights

Net weight	0.6 a

# **Environmental Product Compliance**

REACH SVHC Lead 7439-92-1

#### **Material data**

Colour	orange	Colour chart (similar)	RAL 2000
Storage temperature, min.	-40 °C	Storage temperature, max.	70 °C
Operating temperature, min.	-50 °C	Operating temperature, max.	100 °C
Temperature range, installation, min.	-25 °C	Temperature range, installation, max.	100 °C

#### Rated data acc. to IEC

tantad oan to stomeloud	IEC 60664 1 IEC 61004
tested acc. to standard	IEC 60664-1, IEC 61984

#### **Packing**

Packaging	Box	VPE length	15 mm
VPE width	50 mm	VPE height	80 mm

#### Classifications

ETIM 6.0	EC002943	ETIM 7.0	EC002943
ECLASS 9.0	27-44-04-92	ECLASS 9.1	27-44-04-92
ECLASS 10.0	27-44-04-92	ECLASS 11.0	27-46-04-05

#### Important note

IPC conformity	Conformity: The products are developed, manufactured and delivered according international recognized
	standards and norms and comply with the assured properties in the data sheet resp. fulfill decorative properties
	in accordance with IPC-A-610 "Class 2". Further claims on the products can be evaluated on request.
Notes	<ul> <li>Long term storage of the product with average temperature of 50 °C and average humidity 70% 36 months</li> </ul>

#### **Approvals**

Approvals



ROHS Conform



## **SLA BB11R OR SO**

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Drawings**

## **Example of use**

