

THM WO VIN 49.5/57.1 WS**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Similar to illustration

THM WriteOn cable markers on reels are used for labelling conductors and cables with an outside diameter of up to 36 mm. The transparent adhesive strip fixes and protects the printing on the marker surface.

- Protection of the marking against dirt and abrasion by wrapping it with the transparent adhesive strip
- Simple and quick printing with the high-quality thermal transfer printers

General ordering data

Version	THM, Conductor and cable markers, 6 - 12.1 mm, {Reference (AttributeDefinition) not found: pAttr74196859207437}, white
Order No.	1882900000
Type	THM WO VIN 49.5/57.1 WS
GTIN (EAN)	4032248486991
Qty.	1 pc(s).
compatible printer	2599430000 2599440000

Creation date March 26, 2021 3:00:55 AM CET

THM WO VIN 49.5/57.1 WS

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	0.065 mm	Depth (inches)	0.003 inch
Height	49.53 mm	Height (inches)	1.95 inch
Net weight	632 g	Width	57.1 mm
Width (inches)	2.248 inch		

Temperatures

Operating temperature range	-40...80 °C
-----------------------------	-------------

General data

Adhesive	Polyacrylate adhesive	Approval acc. to UL 969	Yes
Colour	white	Halogen	Yes
Material	Vinyl film	Material colour according to resistance code	9
Number of markers per combination	1 Label reel = Conductor and cable markers	Number per roll	1,000 ST
Operating temperature range	-40...80 °C	Operating temperature range, max.	80 °C
Operating temperature range, min.	-40 °C	Size of labelling field	19.05 x 49.53 mm
Type of printing	neutral	UL 94 flammability rating	V-0
Version	Self-adhesive	Width	57.1 mm

Conductor and cable markers

Conductor O.D.	6 - 12.1 mm	Conductor O.D., max.	12.1 mm
Conductor O.D., min.	6 mm	Conductor cross-section, max.	400 mm ²
Conductor cross-section, min.	0.75 mm ²	Cross-section for connected wire	0.75 - 400 mm ²
Halogen	Yes	Text field height	19.05 mm
Text field width	49.53 mm		

Classifications

ETIM 6.0	EC001530	ETIM 7.0	EC001530
ECLASS 9.0	27-40-04-01	ECLASS 9.1	27-40-04-01
ECLASS 10.0	27-40-04-01	ECLASS 11.0	27-28-11-02

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	STEP
Engineering Data	EPLAN, WSCAD

THM WO VIN 49.5/57.1 WS

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

