Vacuum suction cup ESS-10-CS Part number: 189399





General operating condition

Data sheet

| Feature | Value |
|---|--|
| Suction cup height compensation | 3.3 mm |
| Min. workpiece radius | 25 mm |
| Nominal width | 2 mm |
| Suction cup diameter | 10 mm |
| Suction cup volume | 0.29 cm ³ |
| Connection position | Тор |
| Mounting position | Any |
| Symbol | 00991485 |
| Classification of suction cup holder | Size 3 |
| Suction cup shape | Round bellows, 3.5 convolutions |
| Operating pressure | -0.095 MPa 0 MPa |
| Operating pressure | -0.95 bar 0 bar |
| Operating pressure | -13.775 psi 0 psi |
| Nominal operating pressure | -0.07 MPa |
| Nominal operating pressure | -0.7 bar |
| Nominal operating pressure | -10.15 psi |
| Operating medium | Atmospheric air based on ISO 8573-1:2010 [7:-:-] |
| Corrosion resistance class (CRC) | 1 - Low corrosion stress |
| LABS (PWIS) conformity | VDMA24364 zone III |
| For use in the food industry | See supplementary material information |
| Ambient temperature | -30 °C 180 °C |
| Holding force at nominal operating pressure | 3.9 N |
| Lateral force at nominal operating pressure | 1 N |
| Product weight | 1.6 g |
| Type of mounting | Via vacuum connection |
| Vacuum connection | M4 |
| Color | Transparent |
| Shore hardness | 50 +/- 5 |
| Material of screwed plug | Brass, nickel-plated |
| Note on materials | RoHS-compliant |
| Suction cup material | VMQ (silicone) |