

PAP PDU6/10/3AN**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Product image****Spring connection with PUSH IN Technology**

The innovative PUSH IN technology reduces the amount of time you spend on wiring to a minimum. Direct insertion guarantees high conductor pull-out forces and simple handling for all conductor types.

General ordering data

Version	P-series, End plate, dark beige, 2.5 mm
Order No.	1896340000
Type	PAP PDU6/10/3AN
GTIN (EAN)	4032248511457
Qty.	20 pc(s).
Delivery status	This article will no longer be available in the future.
Available until	2023-03-31
Alternative product	1991940000

Creation date March 26, 2021 6:00:56 AM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

PAP PDU6/10/3AN

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	32.55 mm	Depth (inches)	1.281 inch
Height	80.74 mm	Height (inches)	3.179 inch
Net weight	4.15 g	Width	2.5 mm
Width (inches)	0.098 inch		

Temperatures

Storage temperature	-25 °C...55 °C	Continuous operating temp., min.	-50 °C
Continuous operating temp., max.	120 °C		

Material data

Material	Wemid	Colour	dark beige
UL 94 flammability rating	V-0		

System specifications

Version	End plate
---------	-----------

Additional technical data

Installation advice	Direct mounting	Snap-on	Yes
Type of mounting	Direct mounting		

General

Installation advice	Direct mounting
---------------------	-----------------

Classifications

ETIM 6.0	EC000886	ETIM 7.0	EC000886
ECLASS 9.1	27-14-11-33	ECLASS 10.0	27-14-11-33
ECLASS 11.0	27-14-11-33		

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	STEP
Engineering Data	EPLAN, WSCAD, Zuken E3.S
User Documentation	StorageConditionsTerminalBlocks