



Main

Range of product	Acti 9
Product or component type	Shunt trip release with OC contact
Device short name	MX + OF
Signal contacts composition	1 C/O
[Ie] rated operational current	3 A at ≥ 240 V AC 6 A at < 240 V AC 1 A at 130 V DC 2 A at ≤ 48 V DC 6 A at ≤ 24 V AC
[Uc] control circuit voltage	230...415 V AC 50/60 Hz 110...130 V DC
9 mm pitches	4

Complementary

Range compatibility	Vigi NG125 Acti 9 NG125LMA Acti 9 NG125NA Acti 9 NG125
[Ui] rated insulation voltage	690 V AC 50/60 Hz conforming to EN/IEC 60947-5-1
[Uimp] rated impulse withstand voltage	8 kV conforming to EN/IEC 60947-5-1
Local signalling	Action indicator
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
Height	106 mm
Width	33 mm
Depth	78 mm
Product weight	0.129 kg
Electrical durability	10000 cycles conforming to EN/IEC 60947-5-1
Connections - terminals	Plate terminal - 1 cable(s) 0.5...2.5 mm ² - rigid Plate terminal - 1 cable(s) 0.5...1.5 mm ² - flexible Plate terminal - 1 cable(s) 0.5...1.5 mm ² - flexible with ferrule Plate terminal - 2 cable(s) 2.5 mm ² - flexible Plate terminal - 2 cable(s) 2.5 mm ² - rigid Plate terminal - 2 cable(s) 1.5 mm ² - flexible with ferrule
Wire stripping length	10 mm

Tightening torque	1 N.m
Compatibility code	MX + OF

Environment

Standards	EN/IEC 60947-5-1
Product certifications	ASEFA ASTA LCIE KEMA
IP degree of protection	IP20 B conforming to EN/IEC 60947-5-1 IP4 conforming to EN/IEC 60947-5-1
Pollution degree	3 conforming to EN/IEC 60947-5-1
Overvoltage category	II
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...85 °C

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------