

VG PG42-K67**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Similar to illustration**

In addition to the extensive range of enclosures, Weidmüller offers a variety of cable glands for a wide range of applications.

The cable glands made of brass, plastic and stainless steel meet the most various IP protection classes to suit any industrial enclosure.

Depending on the series of cable glands and the application, the cable glands are approved and tested according to VDE, UL, UR, cULus, DNV GL or EN 45545.

General ordering data

Version	VG K (standard plastic cable gland), Cable glands, PG 42, 13 mm, OD min. 30 - OD max. 38 mm, Polyamide 6
Order No.	1909840000
Type	VG PG42-K67
GTIN (EAN)	4032248536764
Qty.	10 pc(s).

VG PG42-K67

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Length	66.5 mm	Length (inches)	2.618 inch
Net weight	78 g		

General information

AF size 1	60 mm	Cable glands	PG
External thread	PG 42	Length of thread	13 mm
Material	Polyamide 6	Operating temperature range, max.	100 °C
Operating temperature range, min.	-20 °C	Outer cable diameter, max.	38 mm
Outer cable diameter, min.	30 mm	Protection degree	IP67
Seal insert	NBR	Tightening torque	14 Nm
Torque for cap nut, max.	19 Nm	Torque for cap nut, min.	17 Nm
Torque for connecting adapter, max.	16 Nm	Torque for connecting adapter, min.	12 Nm
UL 94 flammability rating	V-2		

Classifications

ETIM 6.0	EC000441	ETIM 7.0	EC000441
ECLASS 9.0	27-14-44-32	ECLASS 9.1	27-14-44-32
ECLASS 10.0	27-14-44-32	ECLASS 11.0	27-14-44-32

Approvals

Approvals



ROHS Conform

Downloads

Engineering Data	STEP
Engineering Data	EPLAN, WSCAD