

KSG M40 BN O NI 2 G40**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Similar to illustration**

The KSG is only intended for use when connecting non-armoured cables and lines. When the cable gland is ordered together with a neoprene seal, the seal allows temperatures from -35°C to +90°C. When using a silicone seal, a temperature range of -60°C to +180°C is possible. The O-ring and the cable gland included in the delivery are made from the same material. IP66 or IP68 protection at a depth of 25 metres under water (a pressure of 2.5 bar) is guaranteed when using this sealing material. The KSG is permitted for use with pressure-resistant Ex d encapsulations and increased safety Ex e.

General ordering data

Version	KSG (Klippon standard Ex cable gland), Cable glands, M 40, 16 mm, OD min. 23 - OD max. 32.2 mm, IP66, IP68 - 2.5 bar, Brass, nickel-plated
Order No.	1911590000
Type	KSG M40 BN O NI 2 G40
GTIN (EAN)	4032248539734
Qty.	10 pc(s).

KSG M40 BN O NI 2 G40

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Length	37 mm	Length (inches)	1.457 inch
Net weight	421.7 g		

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Certificate numbers cable gland

Approval conditions	ATEX, IECEX, EAC	Certificate No. (ATEX)	SIRA05ATEX1287X
Certificate No. (IECEX)	IECEXSIR05.0067X	Certificate no. cable gland (EAC)	RU C-DE.HA65.B.00568 20
Identification	ATEX: II 2GD, Ex db IIC Gb, Ex ta IIIC Da and/or II 2 GD, Ex eb IIC Gb, Ex ta IIIC Da, IECEX: Ex db IIC Gb, Ex eb IIC Gb, Ex ta IIIC Da		

General information

AF size 1	55 mm	Cable glands	metric, nickel-plated brass
Explosion protection type	Pressure-resistant Ex d encapsulation, Improved safety Ex e	External thread	M 40
Installation guidelines	See assembly instructions	Length of thread	16 mm
Material	Brass, nickel-plated	O-Ring	NBR
Operating temperature range, max.	90 °C	Operating temperature range, min.	-35 °C
Outer cable diameter, max.	32.2 mm	Outer cable diameter, min.	23 mm
Pitch of thread	1.5 mm	Protection degree	IP66, IP68 - 2.5 bar
Protection degree with GWDR	IP66, IP68 - 2.5 bar	Seal insert	CR
Sealing	CR	Size of protective cap	L55
Water depth	25 m (30 Min.)		

Classifications

ETIM 6.0	EC000441	ETIM 7.0	EC000441
ECLASS 9.0	27-14-44-32	ECLASS 9.1	27-14-44-34
ECLASS 10.0	27-14-44-32	ECLASS 11.0	27-14-44-32

Approvals

Approvals



Approvals	EAC; ATEX; IECEX
ROHS	Conform

KSG M40 BN O NI 2 G40

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Downloads

Approval/Certificate/Document of Conformity	IECEXSIR05.0067X SIRA05ATEX1287X RU C-DE.HA65.B.00568 20 EU Declaration of Conformity - Klippon KSG cable Gland - DoC DE PS2680 160315 004ISS01
Engineering Data	STEP
Engineering Data	EPLAN, WSCAD
User Documentation	Assembly guidelines