

**CLI C 3-30 SDR SG****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

CLI C conductor markers are mounted on unconnected conductors. Four different sizes are available for labelling conductor cross-sections from 0.5 mm<sup>2</sup> to max. 70 mm<sup>2</sup>. The markers are already printed and ready for use. Individual labelling is possible by combining the individual markers.

- Closed markers, reliable and for mounting on unconnected cables
- A special flexible bellow profile ensures a wide application range
- Fast and easy to fit – with minimal effort
- Corresponding accessories make labelling easy
- Permanent, high-quality labelling
- High contrast for optimum legibility

**General ordering data**

|            |                                                                                                                                                |
|------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| Version    | CableLine, Conductor and cable markers, 8 - 16 mm, {Reference (AttributeDefinition) not found: pAttr74196859207437}, To customer specification |
| Order No.  | <a href="#">1912790000</a>                                                                                                                     |
| Type       | CLI C 3-30 SDR SG                                                                                                                              |
| GTIN (EAN) | 4032248542635                                                                                                                                  |
| Qty.       | 100 pc(s).                                                                                                                                     |

Creation date March 26, 2021 7:39:59 AM CET

## CLI C 3-30 SDR SG

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|                |            |                 |            |
|----------------|------------|-----------------|------------|
| Depth          | 17 mm      | Depth (inches)  | 0.669 inch |
| Height         | 30 mm      | Height (inches) | 1.181 inch |
| Net weight     | 3.75 g     | Width           | 11 mm      |
| Width (inches) | 0.433 inch |                 |            |

## Temperatures

|                             |       |
|-----------------------------|-------|
| Operating temperature range | 80 °C |
|-----------------------------|-------|

## General data

|                             |                           |                                   |                            |
|-----------------------------|---------------------------|-----------------------------------|----------------------------|
| Colour                      | To customer specification | Colour of printing                | black                      |
| Halogen                     | Yes                       | Material                          | PVC, soft, without Cadmium |
| Operating temperature range | 80 °C                     | Operating temperature range, max. | 80 °C                      |
| Orientation of print        | horizontal                | Printed characters                | To customer specification  |
| Printing                    | Custom printing           | Printing method                   | Ink jet technology         |
| Type of printing            | To customer specification | UL 94 flammability rating         | V-0                        |
| Version                     | Loop                      | Width                             | 11 mm                      |

## Conductor and cable markers

|                               |                    |                                  |                         |
|-------------------------------|--------------------|----------------------------------|-------------------------|
| Conductor O.D.                | 8 - 16 mm          | Conductor O.D., max.             | 16 mm                   |
| Conductor O.D., min.          | 8 mm               | Conductor cross-section, max.    | 70 mm <sup>2</sup>      |
| Conductor cross-section, min. | 16 mm <sup>2</sup> | Cross-section for connected wire | 16 - 70 mm <sup>2</sup> |
| Halogen                       | Yes                |                                  |                         |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001530    | ETIM 7.0    | EC001530    |
| ECLASS 9.0  | 27-40-04-01 | ECLASS 9.1  | 27-40-04-01 |
| ECLASS 10.0 | 27-40-04-01 | ECLASS 11.0 | 27-28-11-02 |

## Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## Downloads

|                             |                                                                      |
|-----------------------------|----------------------------------------------------------------------|
| Engineering Data            | <a href="#">EPLAN, WSCAD</a>                                         |
| Product Change Notification | <a href="#">PCN CableLine_DE</a><br><a href="#">PCN CableLine_EN</a> |

### CLI C 3-30 SDR SG

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings



Similar to illustration